

1A, 20V - 150V Surface Mount Schottky Barrier Rectifier

FEATURES

- Low power loss, high efficiency
- Ideal for automated placement
- Guard ring for over-voltage protection
- High surge current capability
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21

APPLICATIONS

- Switching mode power supply (SMPS)
- Adapters
- Lighting application
- Converter

MECHANICAL DATA

- Case: DO-214AA (SMB)
- Molding compound meets UL 94V-0 flammability rating
- Moisture sensitivity level: level 1, per J-STD-020
- Packing code with suffix "G" means green compound (halogen-free)
- Part no. with suffix "H" means AEC-Q101 qualified
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 2 whisker test
- Polarity: As marked
- Weight: 0.093 g (approximately)

KEY PARAMETERS		
PARAMETER	VALUE	UNIT
$I_{F(AV)}$	1	A
V_{RRM}	20 - 150	V
I_{FSM}	30	A
Package	DO-214AA (SMB)	
Configuration	Single Die	



DO-214AA (SMB)

ABSOLUTE MAXIMUM RATINGS (T _A = 25°C unless otherwise noted)										
PARAMETER	SYMBOL	SK 12B	SK 13B	SK 14B	SK 15B	SK 16B	SK 19B	SK 110B	SK 115B	UNIT
Marking code on the device		SK 12B	SK 13B	SK 14B	SK 15B	SK 16B	SK 19B	SK 110B	SK 115B	
Repetitive peak reverse voltage	V _{RRM}	20	30	40	50	60	90	100	150	V
Reverse voltage, total rms value	V _{R(RMS)}	14	21	28	35	42	63	70	105	V
Maximum DC blocking voltage	V _{DC}	20	30	40	50	60	90	100	150	V
Forward current	I _{F(AV)}	1								A
Surge peak forward current, 8.3 ms single half sine-wave superimposed on rated load per diode	I _{FSM}	30								A
Critical rate of rise of off-state voltage	dV/dt	10000								V/μs
Junction temperature	T _J	- 55 to +125			- 55 to +150					°C
Storage temperature	T _{STG}	- 55 to +150								°C

THERMAL PERFORMANCE

PARAMETER	SYMBOL	LIMIT	UNIT
Junction-to-lead thermal resistance	$R_{\theta JL}$	25	°C/W

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER		CONDITIONS	SYMBOL	TYP	MAX	UNIT
Forward voltage per diode ⁽¹⁾	SK12B	$I_F = 1\text{A}, T_J = 25^\circ\text{C}$	V_F	-	0.50	V
	SK13B					V
	SK14B					V
	SK15B			-	0.75	V
	SK16B					V
	SK19B					V
	SK110B			-	0.85	V
	SK115B			-	0.95	V
Reverse current @ rated V_R per diode ⁽²⁾	SK12B	$T_J = 25^\circ\text{C}$	I_R	-	0.5	mA
	SK13B					mA
	SK14B					mA
	SK15B					mA
	SK16B					mA
	SK19B			-	0.1	mA
	SK110B					mA
	SK115B					mA
Reverse current @ rated V_R per diode ⁽²⁾	SK12B	$T_J = 100^\circ\text{C}$	I_R	-	10	mA
	SK13B			-		mA
	SK14B			-		mA
	SK15B			-	5	mA
	SK16B					mA
	SK19B					mA
	SK110B			-	-	mA
	SK115B					mA
Reverse current @ rated V_R per diode ⁽²⁾	SK12B	$T_J = 125^\circ\text{C}$	I_R	-	-	mA
	SK13B			-		mA
	SK14B			-		mA
	SK15B			-	-	mA
	SK16B					mA
	SK19B					mA
	SK110B			-	2	mA
	SK115B					mA

Notes:

1. Pulse test with $PW=0.3\text{ ms}$
2. Pulse test with $PW=30\text{ ms}$

ORDERING INFORMATION

PART NO.	PART NO. SUFFIX	PACKING CODE	PACKING CODE SUFFIX(*)	PACKAGE	PACKING
SK1xxB (Note 1)	H	R5	G	SMB	850 / 7" Plastic reel
		R4		SMB	3,000 / 13" Paper reel
		M4		SMB	3,000 / 13" Plastic reel

Note:

1. "x" defines voltage from 20V (SK12B) to 150V (SK115B)

*: Optional available

EXAMPLE P/N

EXAMPLE P/N	PART NO.	PART NO. SUFFIX	PACKING CODE	PACKING CODE SUFFIX	DESCRIPTION
SK16BHR5G	SK16B	H	R5	G	AEC-Q101 qualified Green compound

CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig1. Forward Current Derating Curve




Fig2. Typical Junction Capacitance




Fig3. Typical Reverse Characteristics





Fig4. Typical Forward Characteristics



CHARACTERISTICS CURVES

($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig5. Maximum Non-repetitive Forward Surge Current





Fig6. Typical Transient Thermal Characteristics




PACKAGE OUTLINE DIMENSIONS

DO-214AA (SMB)



DIM.	Unit (mm)		Unit (inch)	
	Min	Max	Min	Max
A	1.95	2.20	0.077	0.087
B	4.05	4.60	0.159	0.181
C	3.30	3.95	0.130	0.156
D	1.95	2.65	0.077	0.104
E	0.75	1.60	0.030	0.063
F	5.10	5.60	0.201	0.220
G	0.05	0.20	0.002	0.008
H	0.15	0.31	0.006	0.012

SUGGESTED PAD LAYOUT



Symbol	Unit (mm)	Unit (inch)
A	2.3	0.091
B	2.5	0.098
C	4.3	0.169
D	1.8	0.071
E	6.8	0.268

MARKING DIAGRAM



P/N = Marking Code
G = Green Compound
YW = Date Code
F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Taiwan Semiconductor:

[SK115B](#) [SK110B](#) [SK12B](#) [SK13B](#) [SK14B](#) [SK15B](#) [SK16B](#) [SK19B R4](#) [SK19B R5](#) [SK13B R5](#) [SK110BHR5](#) [SK13B R4G](#) [SK12B R4G](#) [SK110BHR4](#) [SK15B R5G](#) [SK115BHR5G](#) [SK14BHR4](#) [SK115B R5](#) [SK115BHR4](#) [SK19B R5G](#) [SK12BHR4](#) [SK15B R5](#) [SK115B R4G](#) [SK110B R5](#) [SK19BHR5](#) [SK15BHR4G](#) [SK110BHR5G](#) [SK16BHR5G](#) [SK12BHR5G](#) [SK16B R5](#) [SK15BHR5](#) [SK13BHR4](#) [SK110BHR4G](#) [SK19BHR4G](#) [SK13BHR5](#) [SK115BHR5](#) [SK110B R5G](#) [SK14B R5G](#) [SK110B R4G](#) [SK14BHR4G](#) [SK15BHR5G](#) [SK14B R5](#) [SK13BHR5G](#) [SK16B R4G](#) [SK14BHR5](#) [SK19BHR5G](#) [SK13BHR4G](#) [SK115B R5G](#) [SK14B R4G](#) [SK115BHR4G](#) [SK16BHR4](#) [SK115B R4](#) [SK16B R5G](#) [SK19BHR4](#) [SK19B R4G](#) [SK12BHR5](#) [SK16BHR4G](#) [SK13B R5G](#) [SK15B R4G](#) [SK12BHR4G](#) [SK15BHR4](#) [SK16BHR5](#) [SK12B R5G](#) [SK12B R5](#) [SK14BHR5G](#) [SK15B R4](#) [SK12B R4](#) [SK110B R4](#) [SK14B R4](#) [SK13B R4](#) [SK16B R4](#) [SK16B M4G](#) [SK16B M4](#)