



HW1991ISR-3USB-5

HW19

MOBILE HANDHELD SCANNERS

SICK
Sensor Intelligence.



Ordering information

Type	Part no.
HW1991ISR-3USB-5	2123087

Included in delivery: Base station (1), USB cable (1), HW1991ISR-3 (1)

Other models and accessories → www.sick.com/HW19



Detailed technical data

Features

Version	Standard Range
Application	Industrial application
Scanner design	Wireless variant
Sensor resolution	1,280 px x 800 px
Light source	LED, Visible, Red, 625 nm
Alignment aid	Laser, Red, 655 nm
Reading distance	0 mm ... 837 mm
Code resolution	≥ 0.076 mm ¹⁾ ≥ 0.152 mm ²⁾

¹⁾ Valid for Code 39.

²⁾ Valid for Data Matrix code.

Mechanics/electronics

Supply voltage	4 V DC ... 5.5 V DC
Current consumption	Charging (5 V DC): 1 A Standby: 120 mA
Housing	Plastic (UL 94 V-0)
Housing color	Orange, gray
Enclosure rating	IP65 IP67
Weight	405 g, incl. rechargeable battery
Dimensions (L x W x H)	100 mm x 76 mm x 192 mm

Performance

Readable code structures	1D codes, 2D codes, Stacked, Digimarc®
Bar code types	Code 39, Code 39 Trioptic, Code 32, Code 93, Code 11, Codabar, Code 128, GS1-128 / EAN 128, UPC / EAN / JAN (with addition), MSI/Plessey, UK/Plessey, IATA, Interleaved 2 of 5, Standard and Industrial 2 of 5, Matrix 2 of 5, Telepen, GS1 DataBar, Australian Post, China Post, German Post, US Planet, US Postnet, British Post, Intelligent Mail, Japan Post, Korean Post, Dutch KIX Post

2D code types	Data Matrix, QR code, MicroQR-Code, Aztec, MaxiCode, Digimarc, DOT Code, CodaBlock A/F, GS1, Chinese Sensible Code, OCR symbologies
Stacked code types	PDF417, MicroPDF417, Code 49, Code 16K, Composite, Codablock F
Code alignment	Omni-directional
Horizontal motion tolerance	Typ. 450 cm/s
Battery power	Up to 50,000 scans when fully charged, 14 h continuous operation at 1 scan/s
Code buffer	5,000 Codes (EAN, for scanning in batch mode)

Interfaces

USB	✓
Function	Keyboard wedge, COM-Port emulation
Optical indicators	3 LEDs (good read, charge of battery, radio connection status)
Acoustic indicators	Beeper, can be switched off
Vibration	Yes
Configuration software	EZConfig Tool (≥ V.4.5.35)

Ambient data

Shock resistance	50 drop samples at -30 °C ... +50 °C from 2 m height on concrete 20 drop samples at 25 °C, 55% rel. air humidity onto concrete from a height of 2.4 m Onto concrete from a height of 3 m
Ambient operating temperature	-20 °C ... +50 °C
Storage temperature	-40 °C ... +70 °C
Permissible relative humidity	95 %, Non-condensing
Ambient light immunity	100,000 lx
Bar code print contrast (PCS)	≥ 20 %

General notes

Items supplied	The battery is included in delivery
-----------------------	-------------------------------------


Classifications

ECLASS 5.0	27280101
ECLASS 5.1.4	27280101
ECLASS 6.0	27280101
ECLASS 6.2	27280101
ECLASS 7.0	27280101
ECLASS 8.0	27280101
ECLASS 8.1	27280101
ECLASS 9.0	27280101
ECLASS 10.0	27280101
ECLASS 11.0	27280101
ECLASS 12.0	27280101
ETIM 5.0	EC002550
ETIM 6.0	EC002550
ETIM 7.0	EC002550
ETIM 8.0	EC002550
UNSPSC 16.0901	43211701

Connection diagram


PROFINET IO/RT

PROFINET IO/RT




PROFIBUS DP

PROFIBUS DP




EtherCAT®

EtherCAT®



AUX looping

Looping-in via AUX



Selection Guide




^{*)} For EtherNet/IP third party gateway is required from e.g. Control or HMS (requires local sourcing).

HW1991ISR-3USB-5 | HW19

MOBILE HANDHELD SCANNERS

HW199x



Optional accessories for all scanner versions *)



*) Extract from product portfolio. Other variants are available.

Optional accessories only for cordless scanner versions



Recommended accessories

Other models and accessories → www.sick.com/HW19

	Brief description	Type	Part no.
Rechargeable batteries and battery chargers			
	Charging/Communication station for HW1911 / HW1991, Bluetooth class 1, 100 m, host interfaces: RS-232 / USB / KBW (Honeywell CCB22-100BT-03N)	Base station	4112984
Others			
	Power supply unit with UK male connector for charging station, 1 A, 5.2 V DC, 90 V AC ... 255 V AC at 50 Hz ... 60 Hz (Honeywell PS-05-1000W-G)	Power supply unit	6064642
	Power supply unit with EU male connector for charging station, 1 A, 5.2 V DC, 90 V AC ... 255 V AC at 50 Hz ... 60 Hz (Honeywell PS-05-1000W-C)	Power supply unit	6064641
	Power supply unit with NA male connector for charging station, 1 A, 5.2 V DC, 90 V AC ... 255 V AC at 50 Hz ... 60 Hz (Honeywell PS-05-1000W-A)	Power supply unit	6052582

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is “Sensor Intelligence.”

WORLDWIDE PRESENCE:

Contacts and other locations –www.sick.com