

You are here: [Products](#) » [Heatsinks f.cool](#) » [Profile heatsinks and fluid coolers](#) » [Standard extruded heatsinks](#) » [SK 434 ...](#) » [SK 434](#)



Heatsinks f.cool

- ▼ Profile heatsinks and fluid coolers
 - [Standard extruded heatsinks](#)
 - Extruded heatsinks for lock-in retaining spring
 - Extruded heatsinks for PCB mounting
 - Extruded heatsinks for DC/DC converter
 - Retaining springs for transistors
 - U-Extruded heatsinks
 - Die-cast heatsinks
 - Fin coolers
 - Fluid coolers
 - Aluminium flat-, quadrangular-, angled-, U- & T-profiles
- ▶ Heatsinks and active heatsinks for processors
- ▶ Finger-shaped heatsinks
- ▶ Cooling aggregates
- ▶ Accessories for electronic components
- ▶ **Cases f.case**
- ▶ **Connectors f.con**

Standard extruded heatsinks

SK 434 50 SA

50 x 40 mm

[add to request](#)



Features **Technical Drawing** **Service**

width	50 mm
height	40 mm
plate thickness	10 mm
lengths	50 mm
R_{DS}	1.25 - 3.6 K/W
drilling pattern	SSR 1 SSR 4
surface	black anodised