




由Autodesk教育版产品制作

由Autodesk教育版产品制作



PCB LAYOUT

备注：侧弹分为外弹与内弹

目錄 MAPX
△

設 變 內 容 MODIFICATION
側彈變更

日 期 DATE
2013. 3. 10

NOTES:

Housing: Thermoplastics

Contact: Copper Alloy

Shell: Copper Alloy/Steel

Voltage Current Rating: 1.5 AMP. 30V AC

Insulation Resistance: 1000MΩ Min.

Contact Resistance: 30 MΩ Max.

Dielectric Withstanding Voltage: 500W AC

Temperature Range: -35°C to +85°C

Insulator color: Black/White

Plastic material: PBT/LCP/Others

Shell finish: Nickel plated/Tin-Lead plated

Mechanical:

Mating Force: 3.5KG MAX

Unmating Force: 0.7 KG MIN.

Contact finish:

01: Selective Gold Flash

02: Selective Gold 3U"

03: Selective Gold 5U"

04: Selective Gold 15U"

05: Selective Gold 30U"

产品图
PRODUCT CHART DWG

公差一览表 TOLERANCE UNLESS OTHERWISE			
X.	±0.25	X'.	±5°
.X	±0.20	.X'	±2°
.XX	±0.15	.XX'	±1°
.XXX	±0.10	.XXX'	±0.5°

深圳市精拓金电子有限公司

单位 UNITS	MM	制图 DRAWING	Z-Y-B	产品料号 PRODUCT PART NO.	904-232B2032S10100
比例 SCALE	1:1	审核 CHKD		产品名称 PRODUCT NO.	AF鱼叉脚贴板有边内弹铜壳反向 LCP本色1.2柱
日期 DATE	2014. 10. 20	核准 APPD		角法 VIEW	⊕ ⊖
				版本 VER	A0

由Autodesk教育版产品制作