



REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2025.06.17	阿树




SS-12D10 X X X




Knob Type
L
G

H(mm)
2~12

Colour
Blank:Standard Black
R:Red



- Typical Specifications
- 1.Rating:AC 125V 3A
 - 2.Insulation Resistance:1,000M min
 - 3.Dielectric strength:1,500V RMS
 - 4.Operating Life: 10,000 cycles



SCHEMA
TIC(NON-SHORTING)

5	Terminal	3	Copper Alloy	silver plated
4	Contact	1	Copper Alloy	silver plated
3	Housing	1	Stainless Steel	
2	Slide Handle	1	Nylon	
1	Case	1	Diallyl Phthalate (DAP)	
ITEM	PAPT NAME	QTY	MATERIAL	FINISHING

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERAUCES	



DESIGN	阿树	VIEW:		MODEL TYPE:	SLIDE SWITCH
CHECKED		UNIT:	mm/in	PART NO.:	SS-12D10XXX
APPROVED		SIZE:	A4	DWG NO.:	