



Product: [9463DB](#)

Blue Hose®, 1 Pr #20 Str TC, PE Ins Blu, Clr, Foil+TC Brd, PE Jkt, DIR BUR

[Request Sample](#)

Product Description

Blue Hose® for Data Highway Plus, 1 Pair 20AWG (7x28) Tinned Copper, PE Insulation Blue & Clear, Overall Beldfoil®+Tinned Copper Braid(55%) Shield, Blue PE Outer Jacket, DIR BUR

Technical Specifications

Product Overview

Suitable Applications:	direct burial, harsh environment, Allen Bradley Data Highway communication interface between PLC processors, I/O devices, operator interfaces, computers and other intelligent devices, PLC processor interlocking, peer-to-peer messaging, remote programming, troubleshooting, I/O updates, etc.
------------------------	--

Construction Details

Conductor

Element	No. of Elements	Size	Stranding	Material
Pair(s)	1	20 AWG	7x28	TC - Tinned Copper

Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code	Notes
Pair(s)	PE - Polyethylene	0.019 in (0.48 mm)	0.0755 in (1.92 mm)	Clear & Blue	Twinax with rod fillers

Outer Shield

Shield Type	Material	Coverage	Drainwire Type
Tape	Bi-Laminate (Alum+Poly)	100%	20 AWG (7x28) TC
Braid	Tinned Copper (TC)	55%	

Outer Jacket

Material	Nom. Thickness	Nom. Diameter
PE - Polyethylene	0.032 in (0.81 mm)	0.240 in (6.10 mm)

Overall Cable Diameter (Nominal):

0.240 in (6.10 mm)

Electrical Characteristics

Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedence	Nom. Velocity of Prop.
Pair(s)	9.5 Ohm/1000ft (31 Ohm/km)	19.7 pF/ft (64.6 pF/m)	37 pF/ft	78 Ohm	66%

High Frequency (Nominal/Typical)

Element	Frequency [MHz]	Nom. Insertion Loss (Attenuation)
Pair(s)	1	0.6 dB/100ft
	10	2.1 dB/100ft
	50	5.0 dB/100ft
	100	7.5 dB/100ft
	200	11.0 dB/100ft
	400	16.0 dB/100ft

Mechanical Characteristics

Temperature

Operating
-40°C to 80°C

Bend Radius

Stationary Min.	Installation Min.
2.5 in (64 mm)	2.5 in

Max. Pull Tension:	48 lbs (22 kg)
Bulk Cable Weight:	36 lbs/1000ft (54 kg/km)

Standards and Compliance

Environmental Suitability:	Indoor, Outdoor, Burial
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

History

Update and Revision:	Revision Number: 0.285 Revision Date: 04-30-2024
----------------------	--

Part Numbers

Variants

Item #	Color	UPC	Footnote
9463DB S8Y1000	Blue, Uv	612825253693	C
9463DB S8Y5000	Blue, Uv	612825253709	C

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.