



规格说明:Specifications:
电气特性:Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:
1000MEGA ohms MIN

物理性能:Mechanical:

1. 插拔力: Connector Mate and Unmate Force
Mate force:3.57kgf(MAX)
Unmate force:1.02kgf(MIN)
2. 端子保持力: Terminal Retention
1.2kgf(MIN)

原材料:Material:

1. 塑胶:Housing:
Hing Temperature Tnermaplastics,
UL 94V-0 PBT White/Black
 2. 端子:Contact:Copper Alloy C2680
 3. 外壳:Shell: Copper Alloy C2680/SPCC
- 电镀:Finish:
1. 端子:Contact: Plated Gold in Mating Area;
Tin On Solder Talls
 2. 外壳:Shell:
Nickel Plating

 深圳市万骏达电子有限公司 http://www.wanjunda.com		图号 (DWG NO)	单位 (UNIT): MM
品名 (ITEM NO)	A/F 短体10.0 180度插板卷边	版本 (REV)	比例 (SCALE) 1:1
料号 (PART NO)	USB2.0-AF-ZC-JB-10.0	日期 (DATE)	设计 (DESIGN)
模号 (MODEL NO)		审核 (CHECKED)	未注公差 TOLERANCE UNSPECIFIED X.X ±0.30 X.XX ±0.20 X.XXX ±0.10 X° X' ±5° X.X° ±2°
		核准 (APPROVED)	