


CWR29 - MIL-PRF-55365/11 Established Reliability, COTS-Plus & Space Level



MARKING

(White marking on black body)



Polarity Stripe (+)

Capacitance Code
Rated Voltage

A low ESR version of CWR09 and CWR19 that is fully qualified to MIL-PRF-55365/11, the CWR29 series represents the most flexible of surface mount form factors and the optimum power handling for all filtering applications. It is offered in nine case sizes (the original A through H of CWR09 and adding the new X case size).

The molded body / compliant termination construction ensures no TCE mismatch with any substrate. This construction is compatible with a wide range of SMT board assembly processes including wave or reflow solder, conductive epoxy or compression bonding techniques. The parts also carry full polarity and capacitance / voltage marking.

The five smaller cases are characterized by their low profile construction, with the A case being the world's smallest molded military tantalum chip.

The series is qualified to MIL-PRF-55365 Weibull "B", "C", "D" and "T" levels, with all surge options ("A", "B" & "C") available.

For Space Level applications, AVX SRC 9000 qualification is recommended (see ratings table for part number availability).

There are four termination finishes available: solder plated, fused solder plated, hot solder dipped and gold plated (these are "H", "K", "C" and "B" termination, respectively, per MIL-PRF-55365). In addition, the molding compound has been selected to meet the requirements of UL94V-0 (Flame Retardancy) and outgassing requirements of ASTM E-595.

For moisture sensitivity levels please refer to the High Reliability Tantalum MSL section located in the back of the High Reliability Tantalum Catalog.

CASE DIMENSIONS:

millimeters (inches)

Case Code	Length (L) ±0.38 (0.015)	Width (W) ±0.38 (0.015)	Height (H) ±0.38 (0.015)	Term. Width (W _t)	Term. Length (A) +0.25/-0.13 (+0.010/-0.005)	S min	Typical Weight (g)
A	2.54 (0.100)	1.27 (0.050)	1.27 (0.050)	1.27±0.13 (0.050±0.005)	0.76 (0.030)	0.38 (0.015)	0.016
B	3.81 (0.150)	1.27 (0.050)	1.27 (0.050)	1.27±0.13 (0.050±0.005)	0.76 (0.030)	1.65 (0.065)	0.025
C	5.08 (0.200)	1.27 (0.050)	1.27 (0.050)	1.27±0.13 (0.050±0.005)	0.76 (0.030)	2.92 (0.115)	0.035
D	3.81 (0.150)	2.54 (0.100)	1.27 (0.050)	2.41±0.13/-0.25 (0.095±0.005/-0.010)	0.76 (0.030)	1.65 (0.065)	0.045
E	5.08 (0.200)	2.54 (0.100)	1.27 (0.050)	2.41±0.13/-0.25 (0.095±0.005/-0.010)	0.76 (0.030)	2.92 (0.115)	0.065
F	5.59 (0.220)	3.43 (0.135)	1.78 (0.070)	3.30±0.13 (0.130±0.005)	0.76 (0.030)	3.43 (0.135)	0.125
G	6.73 (0.265)	2.79 (0.110)	2.79 (0.110)	2.67±0.13 (0.105±0.005)	1.27 (0.050)	3.56 (0.140)	0.205
H	7.24 (0.285)	3.81 (0.150)	2.79 (0.110)	3.68±0.13/-0.51 (0.145±0.005/-0.020)	1.27 (0.050)	4.06 (0.160)	0.335
X	6.93 (0.273)	5.41 (0.213)	2.74 (0.108)	3.05±0.13 (0.120±0.005)	1.19 (0.047)	N/A	0.420

CWR29-MIL-PRF 55365/11

CAPACITANCE AND RATED VOLTAGE, V_R (VOLTAGE CODE) RANGE (LETTER DENOTES CASE SIZE)

Capacitance		Rated voltage DC (V _R) at 85°C							
μF	Code	4V (C)	6V (D)	10V (F)	15V (H)	20V (J)	25V (K)	35V (M)	50V (N)
0.10	104								A
0.15	154								A
0.22	224								B
0.33	334						A	A	B
0.47	474					A	A	B	C
0.68	684				A	A/B	B	C	D
1.0	105			A	A	A/B	B/C	D	E
1.5	155		A	A/B	A/B	B/C	D	E	F
2.2	225	A		A/B	A/C	B/D	D/E		F
3.3	335	A	A/B	A/C	B/D	D/E	E	F	G
4.7	475	A/B	A/C	B/C/D	B/C/D/E	E	F	G	H
6.8	685	A/C	B/D	B/C/D/E	D/E	E/F	F/G	G/H	
10	106	B/D	B/E	B/C/D/E	D/E/F	E/F	G	H	
15	156	B/E	B/D/E	D/E/F	E/F	F/G	G/H	X	
22	226	B/D	D/E/F	E	F/G	G/H	G/H		
33	336	D/E/F	E	F/G	F/G/H	H	H		
47	476	E	F/G	F/G/H	G/H	H/X			
68	686	E/G	F/G/H	G	G/H				
100	107	F/H	G	G/H	H				
150	157	G	G	H/X					
220	227	H	H	H					
330	337	H	H						

HOW TO ORDER

COTS-PLUS & MIL QPL (CWR29):

TAZ	H	227	*	006	C	□	#	@	0	^	++
Type	Case Size	Capacitance Code pF code: 1st two digits represent significant figures 3rd digit represents multiplier (number of zeros to follow)	Capacitance Tolerance M = ±20% K = ±10% J = ±5%	Voltage Code 004 = 4Vdc 006 = 6Vdc 010 = 10Vdc 015 = 15Vdc 020 = 20Vdc 025 = 25Vdc 035 = 35Vdc 050 = 50Vdc	Standard or Low ESR Range C = Std ESR L = Low ESR	Packaging B = Bulk R = 7" T&R S = 13" T&R W = Waffle See page 8 for additional packaging options.	Inspection Level S = Std. Conformance L = Group A M = MIL (JAN) CWR29	Reliability Grade Weibull: B = 0.1%/1000 hrs. 90% conf. C = 0.01%/1000 hrs. 90% conf. D = 0.001%/1000 hrs. 90% conf. Z = Non-ER	Qualification Level 0 = N/A T = T Level 9 = SRC9000	Termination Finish H = Solder Plated 0 = Fused Solder Plated 8 = Hot Solder Dipped 9 = Gold Plated 7 = Matte Sn (COTS-Plus only)	Surge Test Option 00 = None 23 = 10 Cycles, +25°C 24 = 10 Cycles, -55°C & +85°C 45 = 10 cycles, -55°C & +85°C before Weibull

CWR29 P/N CROSS REFERENCE:

CWR29	D	^	227	*	@	H	+	□
Type	Voltage Code C = 4Vdc D = 6Vdc F = 10Vdc H = 15Vdc J = 20Vdc K = 25Vdc M = 35Vdc N = 50Vdc	Termination Finish H = Solder Plated K = Solder Fused C = Hot Solder Dipped B = Gold Plated	Capacitance Code pF code: 1st two digits represent significant figures 3rd digit represents multiplier (number of zeros to follow)	Capacitance Tolerance M = ±20% K = ±10% J = ±5%	Reliability Grade Weibull: B = 0.1%/1000 hrs. 90% conf. C = 0.01%/1000 hrs. 90% conf. D = 0.001%/1000 hrs. 90% conf. T = T Level A = Non-ER	Case Size	Surge Test Option A = 10 cycles, +25°C B = 10 cycles, -55°C & +85°C C = 10 cycles, -55°C & +85°C before Weibull Z = None required	Packaging Bulk = Standard 1TR = 13" T&R 1W = Waffle See page 8 for additional packaging options.

SPACE LEVEL OPTIONS TO SRC9000*:

TAZ	H	227	*	006	C	□	L	@	9	^	++
Type	Case Size	Capacitance Code pF code: 1st two digits represent significant figures 3rd digit represents multiplier (number of zeros to follow)	Capacitance Tolerance M = ±20% K = ±10% J = ±5%	Voltage Code 004 = 4Vdc 006 = 6Vdc 010 = 10Vdc 015 = 15Vdc 020 = 20Vdc 025 = 25Vdc 035 = 35Vdc 050 = 50Vdc	Standard or Low ESR Range C = Std ESR L = Low ESR	Packaging B = Bulk R = 7" T&R S = 13" T&R W = Waffle See page 8 for additional packaging options.	Inspection Level L = Group A	Reliability Grade Weibull: B = 0.1%/1000 hrs. 90% conf. C = 0.01%/1000 hrs. 90% conf. D = 0.001%/1000 hrs. 90% conf.	Qualification Level 9 = SRC9000	Termination Finish H = Solder Plated 0 = Fused Solder Plated 8 = Hot Solder Dipped 9 = Gold Plated	Surge Test Option 45 = 10 cycles, -55°C & +85°C before Weibull

*Contact factory for AVX SRC9000 Space Level SCD details.

TECHNICAL SPECIFICATIONS

Technical Data:	Unless otherwise specified, all technical data relate to an ambient temperature of 25°C									
Capacitance Range:	0.10 µF to 330 µF									
Capacitance Tolerance:	±5%; ±10%; ±20%									
Rated Voltage (V _R)	≤ 85°C:	4	6	10	15	20	25	35	50	
Category Voltage (V _C)	≤ 125°C:	2.7	4	6.7	10	13.3	16.7	23.3	33.3	
Surge Voltage (V _S)	≤ 85°C:	5.3	8	13.3	20	26.7	33.3	46.7	66.7	
Surge Voltage (V _S)	≤ 125°C:	3.5	5.3	8.7	13.3	17.8	22.2	31.1	44.5	
Temperature Range:	-55°C to +125°C									

CWR29 - MIL-PRF-55365/11 Established Reliability, COTS-Plus & Space Level



All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5V RMS with a maximum DC bias of 2.2 volts. DCL is measured at rated voltage after 5 minutes.

NOTE: AVX reserves the right to supply a higher voltage rating or tighter tolerance part in the same case size, to the same reliability standards.

CWR29 - MIL-PRF-55365/11 Established Reliability, COTS-Plus & Space Level



All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5V RMS with a maximum DC bias of 2.2 volts. DCL is measured at rated voltage after 5 minutes.

NOTE: AVX reserves the right to supply a higher voltage rating or tighter tolerance part in the same case size, to the same reliability standards.

RATING & PART NUMBER REFERENCE				Parametric Specifications by Rating per MIL-PRF-55365/11										Typical RMS Ripple Data by Rating									
CWR29 P/N		AVX MIL & COTS-Plus P/N		AVX SRC9000 P/N		Case		Cap @ 120kHz µF @ 25°C	DC Rated Voltage @ +85°C V	ESR @ 100kHz Ohms @ +25°C	DCL max +25°C (µA)	+125°C (µA)	+25°C (%)	DF Max +65/125°C (%)	Power Dissipation W	25°C Ripple A (100kHz)	85°C Ripple A (100kHz)	125°C Ripple A (100kHz)	25°C Ripple V (100kHz)	85°C Ripple V (100kHz)	125°C Ripple V (100kHz)		
CWR29/684*0B+0	TAZ B 684 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ B 684 * 020 L □ □ □ □ □ □ □ 9 + +	B	0.68	20	5.6	1	10	12	6	8	8	8	0.070	0.11	0.10	0.04	0.63	0.56	0.25			
CWR29/105*0A+0	TAZ A 105 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ A 105 * 020 L □ □ □ □ □ □ □ 9 + +	A	1	20	7.5	1	10	12	6	8	8	8	0.050	0.08	0.07	0.03	0.61	0.55	0.24			
CWR29/105*0B+0	TAZ B 105 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ B 105 * 020 L □ □ □ □ □ □ □ 9 + +	B	1	20	4.8	1	10	12	6	8	8	8	0.070	0.12	0.11	0.05	0.58	0.52	0.23			
CWR29/155*0B+0	TAZ B 155 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ B 155 * 020 L □ □ □ □ □ □ □ 9 + +	B	1.5	20	3.6	1	10	12	6	8	8	8	0.070	0.14	0.13	0.06	0.50	0.45	0.20			
CWR29/155*0C+0	TAZ C 155 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ C 155 * 020 L □ □ □ □ □ □ □ 9 + +	C	1.5	20	2.4	1	10	12	6	8	8	8	0.075	0.18	0.16	0.07	0.42	0.38	0.17			
CWR29/225*0B+0	TAZ B 225 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ B 225 * 020 L □ □ □ □ □ □ □ 9 + +	B	2.2	20	3.6	1	10	12	6	8	8	8	0.070	0.14	0.13	0.06	0.50	0.45	0.20			
CWR29/225*0C+0	TAZ C 225 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ D 225 * 020 L □ □ □ □ □ □ □ 9 + +	D	2.2	20	1.7	1	10	12	6	8	8	8	0.080	0.22	0.20	0.09	0.37	0.33	0.15			
CWR29/335*0B+0	TAZ D 335 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ D 335 * 020 L □ □ □ □ □ □ □ 9 + +	D	3.3	20	2	1	10	12	6	8	8	8	0.080	0.20	0.18	0.08	0.40	0.36	0.16			
CWR29/335*0E+0	TAZ E 335 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ E 335 * 020 L □ □ □ □ □ □ □ 9 + +	E	3.3	20	1.2	1	10	12	6	8	8	8	0.090	0.27	0.25	0.11	0.33	0.30	0.13			
CWR29/475*0B+0	TAZ E 475 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ E 475 * 020 L □ □ □ □ □ □ □ 9 + +	E	4.7	20	1.7	1	10	12	6	8	8	8	0.090	0.23	0.21	0.09	0.39	0.35	0.16			
CWR29/685*0B+0	TAZ E 685 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ E 685 * 020 L □ □ □ □ □ □ □ 9 + +	E	6.8	20	1.5	2	20	24	6	8	8	8	0.090	0.24	0.22	0.10	0.37	0.33	0.15			
CWR29/685*0F+0	TAZ F 685 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ F 685 * 020 L □ □ □ □ □ □ □ 9 + +	F	6.8	20	0.7	2	20	24	6	8	8	8	0.100	0.38	0.34	0.15	0.26	0.24	0.11			
CWR29/106*0B+0	TAZ F 106 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ F 106 * 020 L □ □ □ □ □ □ □ 9 + +	F	10	20	0.8	2	20	24	6	8	8	8	0.100	0.35	0.32	0.14	0.28	0.25	0.11			
CWR29/156*0B+0	TAZ F 156 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ F 156 * 020 L □ □ □ □ □ □ □ 9 + +	F	15	20	0.8	3	30	36	6	8	8	8	0.100	0.35	0.32	0.14	0.28	0.25	0.11			
CWR29/156*0G+0	TAZ G 156 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ G 156 * 020 L □ □ □ □ □ □ □ 9 + +	G	15	20	0.275	3	30	36	6	8	8	8	0.125	0.67	0.61	0.27	0.19	0.17	0.07			
CWR29/226*0B+0	TAZ G 226 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ G 226 * 020 L □ □ □ □ □ □ □ 9 + +	G	22	20	0.625	4	40	48	6	8	8	8	0.125	0.45	0.40	0.18	0.28	0.25	0.11			
CWR29/226*0H+0	TAZ H 226 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ H 226 * 020 L □ □ □ □ □ □ □ 9 + +	H	22	20	0.18	4	40	48	6	8	8	8	0.150	0.91	0.82	0.37	0.16	0.15	0.07			
CWR29/336*0B+0	TAZ H 336 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ H 336 * 020 L □ □ □ □ □ □ □ 9 + +	H	33	20	0.18	6	60	72	6	8	10	10	0.150	0.91	0.82	0.37	0.16	0.15	0.07			
CWR29/476*0B+0	TAZ H 476 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ H 476 * 020 L □ □ □ □ □ □ □ 9 + +	H	47	20	0.11	10	100	120	8	10	10	10	0.150	0.91	0.82	0.37	0.16	0.15	0.07			
CWR29/476*0X+0	TAZ X 476 * 020 L □ □ □ □ □ □ □ 9 + +	TAZ X 476 * 020 L □ □ □ □ □ □ □ 9 + +	X	47	20	0.11	10	100	120	8	10	10	10	0.200	1.35	1.21	0.54	0.15	0.13	0.06			
CWR29/334*0A+0	TAZ A 334 * 025 L □ □ □ □ □ □ □ 9 + +	TAZ A 334 * 025 L □ □ □ □ □ □ □ 9 + +	A	0.33	25	7.5	1	10	12	6	8	8	8	0.050	0.08	0.07	0.03	0.61	0.55	0.24			
CWR29/474*0A+0	TAZ A 474 * 025 L □ □ □ □ □ □ □ 9 + +	TAZ A 474 * 025 L □ □ □ □ □ □ □ 9 + +	A	0.47	25	7.5	1	10	12	6	8	8	8	0.050	0.08	0.07	0.03	0.61	0.55	0.24			
CWR29/684*0B+0	TAZ B 684 * 025 L □ □ □ □ □ □ □ 9 + +	TAZ B 684 * 025 L □ □ □ □ □ □ □ 9 + +	B	0.68	25	4	1	10	12	6	8	8	8	0.070	0.13	0.12	0.05	0.53	0.48	0.21			
CWR29/105*0B+0	TAZ B 105 * 025 L □ □ □ □ □ □ □ 9 + +	TAZ B 105 * 025 L □ □ □ □ □ □ □ 9 + +	B	1	25	4	1	10	12	6	8	8	8	0.070	0.13	0.12	0.05	0.53	0.48	0.21			
CWR29/105*0C+0	TAZ C 105 * 025 L □ □ □ □ □ □ □ 9 + +	TAZ C 105 * 025 L □ □ □ □ □ □ □ 9 + +	C	1	25	2.6	1	10	12	6	8	8	8	0.075	0.17	0.15	0.07	0.44	0.40	0.18			
CWR29/155*0B+0	TAZ D 155 * 025 L □ □ □ □ □ □ □ 9 + +	TAZ D 155 * 025 L □ □ □ □ □ □ □ 9 + +	D	1.5	25	1.7	1	10	12	6	8	8	8	0.080	0.22	0.20	0.09	0.37	0.33	0.15			
CWR29/225*0B+0	TAZ D 225 * 025 L □ □ □ □ □ □ □ 9 + +	TAZ D 225 * 025 L □ □ □ □ □ □ □ 9 + +	D	2.2	25	2	1	10	12	6	8	8	8	0.080	0.20	0.18	0.08	0.40	0.36	0.16			
CWR29/225*0E+0	TAZ E 225 * 025 L □ □ □ □ □ □ □ 9 + +	TAZ E 225 * 025 L □ □ □ □ □ □ □ 9 + +	E	2.2	25	1	1	10	12	6	8	8	8	0.090	0.30	0.27	0.12	0.30	0.27	0.12			
CWR29/335*0B+0	TAZ E 335 * 025 L □ □ □ □ □ □ □ 9 + +	TAZ E 335 * 025 L □ □ □ □ □ □ □ 9 + +	E	3.3	25	1.2	1	10	12	6	8	8	8	0.090	0.27	0.25	0.11	0.33	0.30	0.13			
CWR29/475*0B+0	TAZ F 475 * 025 L □ □ □ □ □ □ □ 9 + +	TAZ F 475 * 025 L □ □ □ □ □ □ □ 9 + +	F	4.7	25	0.7	2	20	24	6	8	8	8	0.100	0.38	0.34	0.15	0.26	0.24	0.11			
CWR29/685*0B+0	TAZ F 685 * 025 L □ □ □ □ □ □ □ 9 + +	TAZ F 685 * 025 L □ □ □ □ □ □ □ 9 + +	F	6.8	25	0.8	2	20	24	6	8	8	8	0.100	0.35	0.32	0.14	0.28	0.25	0.11			
CWR29/685*0G+0	TAZ G 685 * 025 L □ □ □ □ □ □ □ 9 + +	TAZ G 685 * 025 L □ □ □ □ □ □ □ 9 + +	G	6.8	25	0.3	2	20	24	6	8	8	8	0.125	0.65	0.58	0.26	0.19	0.17	0.08			
CWR29/106*0B+0	TAZ G 106 * 025 L □ □ □ □ □ □ □ 9 + +	TAZ G 106 * 025 L □ □ □ □ □ □ □ 9 + +	G	10	25	0.35	3	30	36	6	8	8	8	0.125	0.60	0.54	0.24	0.21	0.19	0.08			
CWR29/156*0B+0	TAZ G 156 * 025 L □ □ □ □ □ □ □ 9 + +	TAZ G 156 * 025 L □ □ □ □ □ □ □ 9 + +	G	15	25	0.35	4	40	48	6	8	8	8	0.125	0.60	0.54	0.24	0.21	0.19	0.08			
CWR29/156*0H+0	TAZ H 156 * 025 L □ □ □ □ □ □ □ 9 + +	TAZ H 156 * 025 L □ □ □ □ □ □ □ 9 + +	H	15	25	0.2	4	40	48	6	8	8	8	0.150	0.87	0.78	0.35	0.17	0.16	0.07			
CWR29/226*0B+0	TAZ H 226 * 025 L □ □ □ □ □ □ □ 9 + +	TAZ H 226 * 025 L □ □ □ □ □ □ □ 9 + +	H	22	25	0.35	6	60	72	6	8	8	8	0.125	0.60	0.54	0.24	0.21	0.19	0.08			
CWR29/226*0H+0	TAZ H 226 * 025 L □ □ □ □ □ □ □ 9 + +	TAZ H 226 * 025 L □ □ □ □ □ □ □ 9 + +	H	22	25	0.18	6	60	72	6	8	8	8	0.150	0.91	0.82	0.37	0.16	0.15	0.07			
CWR29/336*0B+0	TAZ H 336 * 025 L □ □ □ □ □ □ □ 9 + +	TAZ H 336 * 025 L □ □ □ □ □ □ □ 9 + +	H	33	25	0.18	10	100	120	8	10	10	10	0.150	0.91	0.82	0.37	0.16	0.15	0.07			
CWR29/224*0A+0	TAZ A 224 * 035 L □ □ □ □ □ □ □ 9 + +	TAZ A 224 * 035 L □ □ □ □ □ □ □ 9 + +	A	0.22	35	12	1	10	12	6	8	8	8	0.050	0.06	0.05	0.03	0.77	0.70	0.31			
CWR29/334*0A+0	TAZ A 334 * 035 L □ □ □ □ □ □ □ 9 + +	TAZ A 334 * 035 L □ □ □ □ □ □ □ 9 + +	A	0.33	35	12	1	10	12	6	8	8	8	0.050	0.06	0.05	0.03	0.77	0.70	0.31			
CWR29/474*0B+0	TAZ B 474 * 035 L □ □ □ □ □ □ □ 9 + +	TAZ B 474 * 035 L □ □ □ □ □ □ □ 9 + +	B	0.47	35	6.8	1	10	12	6	8	8	8	0.070	0.10	0.09	0.04	0.69	0.62	0.28			
CWR29/684*0C+0	TAZ C 684 * 035 L □ □ □ □ □ □ □ 9 + +	TAZ C 684 * 035 L □ □ □ □ □ □ □ 9 + +	C	0.68	35	4	1	10	12	6	8	8	8	0.075	0.14	0.12	0.05	0.55	0.49	0.22			
CWR29/105*0B+0	TAZ D 105 * 035 L □ □ □ □ □ □ □ 9 + +	TAZ D 105 * 035 L □ □ □ □ □ □ □ 9 + +	D	1	35	2.2	1	10	12	6	8	8	8	0.080	0.19	0.17	0.08	0.42	0.38	0.17			
CWR29/155*0B+0	TAZ E 155 * 035 L □ □ □ □ □ □ □ 9 + +	TAZ E 155 * 035 L □ □ □ □ □ □ □ 9 + +	E	1.5	35	1.3	1	10	12	6	8	8	8	0.090	0.26	0.24	0.11	0.34	0.31	0.14			
CWR29/335*0B+0	TAZ F 335 * 035 L □ □ □ □ □ □ □ 9 + +	TAZ F 335 * 035 L □ □ □ □ □ □ □ 9 + +	F	3.3	35	0.7	1	10	12	6	8	8	8	0.100	0.38	0.34	0.15	0.26	0.24	0.11			
CWR29/475*0B+0	TAZ G 475 * 035 L □ □ □ □ □ □ □ 9 + +	TAZ G 475 * 035 L □ □ □ □ □ □ □ 9 + +	G	4.7	35	0.375	2	20	24	6	8	8	8	0.125	0.58	0.52	0.23	0.22	0.19	0.09			
CWR29/685*0B+0	TAZ H 685 * 035 L □ □ □ □ □ □ □ 9 + +	TAZ H 685 * 035 L □ □ □ □ □ □ □ 9 + +	G	6.8	35	0.375	3	30	36	6	8	8	8	0.125	0.58	0.52	0.23	0.22	0.19	0.09			
CWR29/685*0H+0	TAZ H 685 * 035 L □ □ □ □ □ □ □ 9 + +	TAZ H 685 * 035 L □ □ □ □ □ □ □ 9 + +	H	6.8	35	0.5	3	30	36	6	8	8	8	0.150	0.55	0.49	0.22	0.27	0.25	0.11			
CWR29/106*0B+0	TAZ H 106 * 035 L □ □ □ □ □ □ □ 9 + +	TAZ H 106 * 035 L □ □ □ □ □ □ □ 9 + +	H	10	35	0.5	4	40	48	8	10	10	10	0.150	0.55	0.49	0.22	0.27	0.25	0.11			
CWR29/156*0B+0	TAZ X 156 * 035 L □ □ □ □ □ □ □ 9 + +	TAZ X 156 * 035 L □ □ □ □ □ □ □ 9 + +	X	15	35	0.19	6	60	72	6	8	8	8	0.200	1.03	0.92	0.41						

All technical data relates to an ambient temperature of +25°C. Capacitance and DF are measured at 120Hz, 0.5V RMS with a maximum DC bias of 2.2 volts. DCL is measured at rated voltage after 5 minutes.

NOTE: AVX reserves the right to supply a higher voltage rating or tighter tolerance part in the same case size, to the same reliability standards.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[AVX:](#)

[CWR29HC107KBHC](#)