



Relays & Contactors > Contactors > Mil-Aero Contactors > DC Contactors



Contact Arrangement: 1 Form X SPST-NO-DM

Wire Size: .34 mm²

Contact Current Rating: 500 A

Coil Resistance: 145 Ω

Features

Configuration Features

Auxiliary Switch Contact Arrangement	None
Contact Arrangement	1 Form X SPST-NO-DM
Contact Number of Poles	1

Electrical Characteristics

Contact Current Rating	500 A
Coil Resistance	145 Ω
Coil Voltage Rating	48 VDC
Contact Switching Voltage (Max)	900 VDC

Body Features

Enclosure Type	Sealed
----------------	--------

Termination Features

Main Termination & Connection Type	M8 x 1.25
Coil Termination & Connection Type	10-32 Stud

Mechanical Attachment

Torque (Main)	80 – 100 in-lbs
Torque (Coil)	15 – 30 in-lbs
Product Mount Type	Chassis

Dimensions



Wire Size	.34 mm²
-----------	---------

Operation/Application

Current Type	DC
--------------	----

Packaging Features

Packaging Method	Individual
------------------	------------

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2023 (233) SVHC > Threshold: Cd (7.5% in component part) Article Safe Usage Statements: Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1-1618002-9
EV200HDANA=RELAY, SPST-NO

TE Part # 4-1618413-3
LEV200ALNAA=CONTACTOR, 110VDC

Also in the Series | Kilovac LEV200

DC Contactors(15)

Definite Purpose Contactors(1)

General Purpose Contactors(4)

High Voltage Relays(13)

Customers Also Bought

TE Part #1-1625984-1
HSA50 15R 5%

TE Part #DRCP25-86PAA-G005
HDR, 86P, BLK, ST, 12/20, SN/NI/CU, AA

TE Part #DRCP25-86PBB-GC05
HDR, 86P, BLK, ST, 12/20, SN/NI/CU, BB

TE Part #SM1-25
STRING POT, 25 INCH RANGE

TE Part #2107373-1
Mechanical Connectors & Repair Sleeves

TE Part #1SNA199219R0300
D4/6.T1

TE Part #640347-1
UMNL SOK 24-18 L/P

TE Part #1951721-2
BSMB-300-500-ENERCON

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5-1618388-8_D.2d_dxf.zip

English



Customer View Model

[ENG_CVM_CVM_5-1618388-8_D.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_5-1618388-8_D.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

[5-1773450-5_sec7_LEV200](#)

English