DT04-08PB-E003 ACTIVE

DEUTSCH | DEUTSCH DT

TE Internal #: DT04-08PB-E003

Housing for Female Terminals, Wire-to-Wire, 8 Position, 9.09 mm [. 358 in] Centerline, Sealable, Black, Wire & Cable, Power, DEUTSCH

DT

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH DT Receptacle Connectors











Connector System: Wire-to-Wire

Number of Positions: 8

Connector & Housing Type: Housing for Female Terminals

Centerline (Pitch): 9.09 mm [.358 in]

Sealable: Yes

All DEUTSCH DT Receptacle Connectors (231)

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Integrated in Housing
Configuration Features	
Blank Cavity Position	0
Connector Modification	End Cap
Number of Positions	8
Number of Rows	2



Electrical Characteristics

Operating Voltage	250 VAC
Nominal Voltage Architecture	250 V

Body Features

Cable Exit Angle	180°
Primary Product Color	Black
Connector & Keying Code	В

Contact Features

Contact Size	Size 16
Contact Type	Receptacle
Mating Pin Diameter	1.57 mm[.062 in]
Contact Current Rating (Max)	13 A

Mechanical Attachment

Terminal Position Assurance	Yes
Strain Relief	Add By Accessory
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PA GF
Centerline (Pitch)	9.09 mm[.358 in]

Dimensions

Connector Height	23.88 mm[.94 in]
Product Width	36.45 mm[1.435 in]
Product Length	46.94 mm[1.848 in]
Row-to-Row Spacing	4.45 mm[.175 in]
Compatible Insulation Diameter Range	2.23 – 3.68 mm[.088 – .145 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]

Operation/Application

Circuit Application Po	ower
------------------------	------



Industry Standards

Degree of Protection	IP68, IP6K9K
Compatible With Agency/Standards Products	SAE J2030
UL Flammability Rating	12mm Flame Test per Standard UL-94
Packaging Features	
Packaging Quantity	300
Packaging Method	Box
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # CAT-J41-DDPC **DEUTSCH DT Plug Connectors**



TE Part # CAT-D48-SP729 DEUTSCH Sealing Plugs



TE Part # CAT-D48-ST273 **DEUTSCH Solid Contacts**



TE Part # CAT-D487-M8649 DEUTSCH DT Mounting Clips



TE Part # W8P WEDGE LOCK, 8P, REC, GRN, DT



TE Part # CAT-J67-DSCC16 DEUTSCH Size 16 Crimp Contacts



TE Part # DT-RT1 EXT TOOL, FRONT RELEASE



TE Part # 2300908-1 0460-003-16329, PIN, SOLID, 20-24AWG, AU



TE Part # CAT-D487-CH8172 DEUTSCH DT Series Housings & Connectors

TE Part # CAT-D48-SFT273 **DEUTSCH Stamped and Formed** Contacts

Also in the Series | DEUTSCH DT





Automotive Connector Caps & Covers



Automotive Connector Locks & Position Assurance(88)



Automotive Housings(711)



Connector Backshells(65)



Connector Seals & Cavity Plugs(9)



Connector Strain Relief(28)



Insertion & Extraction Tools(3)



Other Automotive Connector Accessories(28)





Customers Also Bought





Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_DT04-08PB-E003_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_DT04-08PB-E003_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DT04-08PB-E003_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

TERMINALS AND CONNECTORS

English

ICT Terminals and Connectors Catalogue

English

CONNECTOR SELECTOR

English

Product Specifications

Application Specification

English

Housing for Female Terminals, Wire-to-Wire, 8 Position, 9.09 mm [.358 in] Centerline, Sealable, Black, Wire & Cable, Power, DEUTSCH DT



Agency Approvals

UL Report

English