





特性:

一、电气性能: ELECTRICAL

1. 额定电流: 5.0A
2. 接触阻抗: 40 MILLIOMHS MAX
3. 耐电压: 150V AC / 1 mA MAX
4. 绝缘阻抗: 150V DC/100 MEGA OHMS MIN

二、机械性能:




1. 插入力: 5~20N
2. 拔出力: 8~20N

三、材料: MATERIAL


1. 塑胶: LCP/PA9T UL94V-0
2. 端子: C7025/C18400 T=0.15MM
3. 外壳: SUS304 T=0.30MM
4. 卡勾: SUS304 T=0.15MM

四、电镀:FINISH

1. 端子：接触点镀金 30°NIN
PIN脚焊接区域镀金 10°NIN 。
2. 外壳：镀镍 50°NIN (盐雾48H)。
- 五、电镀品需做盐雾测试：粘锡面面积达到95%以上。
- 六、SMT回流焊 (峰温 $260^{\circ}\text{C} \pm 5^{\circ}\text{C}$) 不能起泡、炸裂、变色不良 (变形在公差范围以内)。
- 七、工作温度： $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$



RECOMMENDED P.C.B. LAYOUT (俯视图)
TOLERANCE UNSPECIFIED $\pm 0.05\text{mm}$



A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B8	SB12
A6	Dp1	B7	Dm2
A7	DM1	B6	Dp2
A8	S001	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND

 深圳市万骏达电子有限公司 http://www.wanjunda.com		图号 (DWG NO)		单位 (UNIT) : MM
		版本 (REV)		比例 (SCALE) 1:1
		日期 (DATE)		 
品名 (ITEM NO)	TYPE C 16P立贴17.5	设计 (DESIGN)		未注公差
料号 (PART NO)	TPC-16P-LT-17.5-A	审核 (CHECKED)		TOLERANCE UNSPECIFIED X, X X ±0.30 X, X X X ±0.20 X, X X X X ±0.10 X, X X X X X ±0.05 X, X X X X X X ±0.025
模号 (MODEL NO)		核准 (APPROVED)		