

Part Number: 1300060374

Product Description: Mini-Change A-Size Single-Ended Cordset, 3 Poles, Female (Straight) to Pigtail, 16 AWG, Rubber Cable,

0.91m (3.0') Length

Series Number: 130006

Status: Active

Product Category: Circular Industrial

Cordsets

Engineering Number: 103000C01F030



Documents & Resources

Drawings

Drawing 1300060374_sd.pdf

Product Environment Compliance

Compliance

| China RoHS | Not Reviewed |
|--------------------|--------------|
| EU ELV | Not Reviewed |
| Low-Halogen Status | Not Reviewed |
| REACH SVHC | Not Reviewed |
| EU RoHS | Not Reviewed |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|--|
| Category | Circular Industrial Cordsets |
| Series | 130006 |
| Description | Mini-Change A-Size Single-Ended Cordset, 3 Poles, Female (Straight) to Pigtail, 16 AWG, Rubber Cable, 0.91m (3.0') Length |
| IP Rating | IP67 |
| Product Family | Brad Mini-Change Connectors |
| Product Name | Mini-Change |
| Protocol | N/A |
| Region | America |
| Туре | Single Ended |
| UPC | 78678843038 |

Agency

| CSA | LR6837 |
|-----|--------|
| | |

Electrical

| Current - Maximum per Contact | 13.0A |
|-------------------------------|-------|
| Voltage - Maximum | 600V |

Physical

| Cable Diameter | 10.67mm (.420") |
|-------------------------|-----------------|
| Cable Length | 0.91m (3.0') |
| Color - Cable Jacket | Yellow |
| Connector End A | Mini-Change |
| Connector End B | Pigtail |
| Coupling Style | Threaded |
| Gender | Female-Pigtail |
| Keyway | Single |
| LED Indicator | No |
| Material - Cable Jacket | Rubber |

| Material - Connector Body | PVC |
|-------------------------------|-------------------------|
| Material - Contact | Copper Alloy |
| Material - Coupling Nut | Black Epoxy Coated Zinc |
| Material - Plating Mating | Gold |
| Net Weight | 654.000/g |
| Orientation | Straight to Pigtail |
| Poles | 3 |
| Temperature Range - Operating | -20° to +90°C |
| Wire/Cable Type | SOO |
| Wire Size (AWG) | 16 |

This document was generated on Sep 25, 2024