



MQS

TE Internal #: 1-1418775-1

Housing for Female Terminals, Wire-to-Board / Wire-to-Wire, 5 Position, 2.54 mm [.1 in] Centerline, Black, Wire & Cable, Signal

[View on TE.com >](#)

Connectors > Automotive Connectors > Automotive Housings > MQS, CONNECTOR HOUSING



Connector System: **Wire-to-Board, Wire-to-Wire**

Number of Positions: **5**

Connector & Housing Type: **Housing for Female Terminals**

Centerline (Pitch): **2.54 mm [.1 in]**

Sealable: **No**

[All MQS, CONNECTOR HOUSING \(360\)](#)

Features

Product Type Features

|                                   |                              |
|-----------------------------------|------------------------------|
| Mixed & Hybrid Connector          | No                           |
| Connector Shape                   | Rectangular                  |
| Connector System                  | Wire-to-Board, Wire-to-Wire  |
| Connector & Housing Type          | Housing for Female Terminals |
| Sealable                          | No                           |
| Connector & Contact Terminates To | Wire & Cable                 |
| Primary Locking Feature           | On the Terminal              |

Configuration Features

|                     |   |
|---------------------|---|
| Number of Positions | 5 |
| Number of Rows      | 1 |

Electrical Characteristics

|                              |            |
|------------------------------|------------|
| Operating Voltage            | 12 VDC     |
| Nominal Voltage Architecture | 12 V, 24 V |

Body Features

|                         |         |
|-------------------------|---------|
| Cable Exit Angle        | 180°    |
| Primary Product Color   | Black   |
| Connector & Keying Code | Neutral |



Contact Features

|                              |                 |
|------------------------------|-----------------|
| Contact Size                 | .63mm           |
| Contact Type                 | Receptacle      |
| Mating Tab Width             | .63 mm[.025 in] |
| Contact Current Rating (Max) | 7.5 A           |

Mechanical Attachment

|                             |                            |
|-----------------------------|----------------------------|
| Terminal Position Assurance | Yes                        |
| Strain Relief               | Without                    |
| Mating Alignment Type       | Polarized                  |
| Mating Alignment            | With                       |
| Connector Mounting Type     | Cable Mount (Free-Hanging) |

Housing Features

|                    |                |
|--------------------|----------------|
| Housing Material   | PBT GF         |
| Centerline (Pitch) | 2.54 mm[.1 in] |

Dimensions

|                  |                 |
|------------------|-----------------|
| Connector Height | 4.5 mm[.177 in] |
| Product Width    | 16.5 mm[.65 in] |

Usage Conditions

|                             |                            |
|-----------------------------|----------------------------|
| Operating Temperature (Max) | 120 °C[248 °F]             |
| Operating Temperature Range | -40 – 120 °C[-40 – 248 °F] |

Operation/Application

|                     |        |
|---------------------|--------|
| Circuit Application | Signal |
|---------------------|--------|

Industry Standards

|                        |         |
|------------------------|---------|
| UL Flammability Rating | UL 94HB |
|------------------------|---------|

Packaging Features

|                  |     |
|------------------|-----|
| Packaging Method | Box |
|------------------|-----|

Other

|                                      |     |
|--------------------------------------|-----|
| Serviceable                          | Yes |
| Connector Position Assurance Capable | No  |

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>



|                                               |                                                                                                                                 |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                       |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                       |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                         |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2024 (241)<br>Candidate List Declared Against: JUNE 2024 (241)<br>Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free                                             |
| Solder Process Capability                     | Not applicable for solder process capability                                                                                    |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # CAT-M8793-T273  
MQS, RECEPTACLE AND TAB

TE Part # CAT-M8793-CH8172  
MQS, CONNECTOR HOUSING

TE Part # 1418776-1  
COVER, MQS, 5 POS.

TE Part # 1418776-2  
COVER, MQS, 5 POS.

Customers Also Bought



TE Part #1473407-1  
025 G 12POS CAP ASSY W TO W

TE Part #1-1418778-1  
MQS, CONNECTOR HOUSING

TE Part #1801175-7  
2W RECEPTACLE HP CONNECTOR  
WHITE

TE Part #1-2299987-2  
65W SEAL PLUG,CONN KIT

TE Part #2109517-1  
025/060/110 HYB 25P CAP ASSY

TE Part #2325415-2  
40POS,ML .025,REC HSG ASSY,UNSLD

TE Part #2411042-1  
TAB0.64X0.64,TERMINAL,025 TAB  
CONTACT

TE Part #474126-E  
SRCP 1,27 3 M 1-KS SMD 137 E1 094 \*  
GU-H

TE Part #3-1437837-1  
WIRING RETAINER, EOV B13A506CA

Documents

Product Drawings  
5POS MQS REC

English

CAD Files  
Customer View Model  
ENG\_CVM\_CVM\_1-1418775-1\_A.2d\_dxf.zip

English

3D PDF

3D

Customer View Model  
ENG\_CVM\_CVM\_1-1418775-1\_A.3d\_igs.zip

English

Customer View Model  
ENG\_CVM\_CVM\_1-1418775-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Product Specifications

1-1418775-1

Housing for Female Terminals, Wire-to-Board / Wire-to-Wire, 5 Position, 2.54 mm [.1 in] Centerline, Black, Wire & Cable, Signal



Application Specification

English