

<u>5</u>)

_3.02 [0.119]

Date	SYM	REVISION RECORD	AUTH	DR.	CK.
10/03/14	Α	UPDATED TO ROHS 2 COMPLIANT	T.B.	B.S.	

ROHS 2 COMPLIANT

N0.	PART NAME	MATERIAL		Tolerance	■ MPD Mem	ory Prote	ection Devices, Inc		
1	COVER PVC COVER OVER FIBERBOARD		1	(Except as noted)	noted) 200 Broad Hollow Road, Farmingdale, New York				
2	BLACK WIRE(-)	24 AWG OR 26 AWG, UL-1007, CSA TR-64, 300V, 80°C		decimal			Scale	Drawn By B.S.	
3	RED WIRE (+)	24 AWG OR 26 AWG, UL-1007, CSA TR-64, 300V, 80°C	1	±.5 (.020)					
4	FEMALE SNAP	BRASS NICKLE PLATED	1	1.5 (.020)				Approved By T.B.	
5	MALE SNAP	BRASS NICKLE PLATED	1	Fractional	Title				
			± .8 (.030)	9 VOLT BATTERY SNAP-T STYLE-4" WIRE LEADS					
			Angular	Date	Drawing Number				
			± 3°	10/03/14	BS4T				