

P-Channel Enhancement Mode Power MOSFET

Description


The RM45P20D3 uses advanced trench technology and design to provide excellent $R_{DS(ON)}$ with low gate charge. It can be used in a wide variety of applications.

General Features


- $V_{DS} = -19V, I_D = -45A$
 $R_{DS(ON)} < 7m\Omega @ V_{GS} = -4.5V$
 $R_{DS(ON)} < 9m\Omega @ V_{GS} = -2.5V$
 $R_{DS(ON)} < 12m\Omega @ V_{GS} = -1.8V$
- High density cell design for ultra low R_{dson}
- Fully characterized avalanche voltage and current
- Good stability and uniformity with high E_{AS}
- Excellent package for good heat dissipation

Application

- Load switch
- Battery protection



Schematic diagram



Pin Assignment



DFN 3.3x3.3 EP top view

Package Marking and Ordering Information

Device Marking	Device	Device Package	Reel Size	Tape width	Quantity
45P20	RM45P20D3	DFN 3.3x3.3 EP	-	-	-

Absolute Maximum Ratings ($T_C = 25^\circ C$ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	-19	V
Gate-Source Voltage	V_{GS}	± 12	V
Drain Current-Continuous	I_D	-45	A
Drain Current-Continuous ($T_C = 100^\circ C$)	$I_D (100^\circ C)$	-35	A
Pulsed Drain Current	I_{DM}	-200	A
Maximum Power Dissipation	P_D	80	W
Derating factor		0.64	W/ $^\circ C$
Operating Junction and Storage Temperature Range	T_J, T_{STG}	-55 To 150	$^\circ C$

Thermal Characteristic

Thermal Resistance, Junction-to-Case ^(Note 2)	$R_{\theta JC}$	1.6	$^\circ C/W$
--	-----------------	-----	--------------

Electrical Characteristics (T_C=25°C unless otherwise noted)

Parameter	Symbol	Condition	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V I _D =-250μA	-19	-	-	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =-16V, V _{GS} =0V	-	-	1	μA
Gate-Body Leakage Current	I _{GSS}	V _{GS} =±12V, V _{DS} =0V	-	-	±100	nA
On Characteristics ^(Note 3)						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =-250μA	-0.4	-0.6	-1.0	V
Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} =-4.5V, I _D =-20A	-	5.8	7	mΩ
		V _{GS} =-2.5V, I _D =-20A	-	7.2	9	
		V _{GS} =-1.8V, I _D =-20A		9	12	
Forward Transconductance	g _{FS}	V _{DS} =-5V, I _D =-20A	80	-	-	S
Dynamic Characteristics ^(Note4)						
Input Capacitance	C _{Iss}	V _{DS} =-10V, V _{GS} =0V, F=1.0MHz	-	3500	-	PF
Output Capacitance	C _{Oss}		-	577	-	PF
Reverse Transfer Capacitance	C _{Rss}		-	445	-	PF
Switching Characteristics ^(Note 4)						
Turn-on Delay Time	t _{d(on)}	V _{DD} =-10V, R _{GEN} =3Ω V _{GS} =-4.5V, R _L =0.5Ω	-	18	-	nS
Turn-on Rise Time	t _r		-	42	-	nS
Turn-Off Delay Time	t _{d(off)}		-	85	-	nS
Turn-Off Fall Time	t _f		-	23	-	nS
Total Gate Charge	Q _g	V _{DS} =-10V, I _D =-20A, V _{GS} =-4.5V	-	55	-	nC
Gate-Source Charge	Q _{gs}		-	10	-	nC
Gate-Drain Charge	Q _{gd}		-	15	-	nC
Drain-Source Diode Characteristics						
Diode Forward Voltage ^(Note 3)	V _{SD}	V _{GS} =0V, I _S =-20A	-	-	-1.2	V
Diode Forward Current ^(Note 2)	I _S		-	-	-45	A
Reverse Recovery Time	t _{rr}	TJ = 25°C, IF = -10A	-	47	-	nS
Reverse Recovery Charge	Q _{rr}	di/dt = 100A/μs ^(Note3)	-	53	-	nC
Forward Turn-On Time	t _{on}	Intrinsic turn-on time is negligible (turn-on is dominated by LS+LD)				

Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature.
2. Surface Mounted on FR4 Board, t ≤ 10 sec.
3. Pulse Test: Pulse Width ≤ 300μs, Duty Cycle ≤ 2%.
4. Guaranteed by design, not subject to production

RATING AND CHARACTERISTICS CURVES (RM45P20D3)




Figure 1 Output Characteristics




Figure 4 R_{DS(on)}-Junction Temperature




Figure 2 Transfer Characteristics




Figure 5 Gate Charge




Figure 3 R_{DS(on)}- Drain Current






Figure 6 Source- Drain Diode Forward


RATING AND CHARACTERISTICS CURVES (RM45P20D3)




-Vds Drain-Source Voltage (V)
Figure 7 Capacitance vs Vds



T_J -Junction Temperature(°C)
Figure 9 Power De-rating



-Vds Drain-Source Voltage (V)
Figure 8 Safe Operation Area



T_J -Junction Temperature(°C)
Figure 10 -Current De-rating





Figure 11 Normalized Maximum Transient Thermal Impedance

DFN3.3X3.3 EP Package Information

封装外形尺寸图				
	符号	单位: mm		
		MIN	MAX	TYP
	A	0.75	0.85	0.8
	B	0.25	0.35	0.3
	C	0.18	0.22	0.2
	D	3.2	3.3	3.25
	E	3.2	3.3	3.25
	F	2.2	2.5	2.35
	G	1.8	2.0	1.9
	H	0.3	0.4	0.35
	I	0.15	0.25	0.2
	J	0.4	0.5	0.45
	K	0.6	0.7	0.65
	L	1.38	1.58	1.48
	M	1.8	2.1	1.95
N	0.15*45°			
O	0.4	0.5	0.45	

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Rectron:](#)

[RM45P20D3](#)