

This document was generated on 06/09/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0432498926

Status: Active

Overview: Modular Jacks and Plugs

Description: Modular Jack, Right Angle, Low Profile, 8/8, Panel Stops

Documents:

3D Model Packaging Specification PK-44050-004 (PDF)
Drawing (PDF) RoHS Certificate of Compliance (PDF)

Product Specification PSX-43249 (PDF)

Agency Certification

CSA LR19980 UL E107635

General

Product Family Modular Jacks/Plugs

Series 43249
Component Type PCB Jack
Magnetic No

Overview <u>Modular Jacks and Plugs</u>

Performance Category 3, 4
Power over Ethernet (PoE) N/A
Product Name RJ45

UPC 800756395500

Physical

Lightpipes/LEDs

Boot Color N/A
Color - Resin Black
Durability (mating cycles max) 500
Flammability 94V-0
Inverted / Top Latch No
Jack Height 13.00mm

Material - Metal Phosphor Bronze

Material - Plating Mating Gold Material - Plating Termination Tin

Material - Resin High Temperature Thermoplastic

None

Orientation Right Angle (Side Entry)

PCB Locator Yes **PCB** Retention Yes PCB Thickness - Recommended 1.57mm Packaging Type Trav Pitch - Mating Interface 1.02mm Pitch - Termination Interface 1.27mm Plating min - Mating 1.270µm Plating min - Termination 2.540µm Ports 1 Positions / Loaded Contacts 8/8

Surface Mount Compatible (SMC)

Temperature Range - Operating


Termination Interface: Style

Yes
-40°C to +85°C
Through Hole

Waterproof / Dustproof No Wire/Cable Type N/A

Electrical

Current - Maximum per Contact 1.5A Grounding to PCB Yes



EU ELV Not Relevant

EU RoHS China RoHS

Not Reviewed REACH SVHC Not Reviewed Halogen-Free Status

Not Reviewed

Need more information on product environmental compliance?

Email <u>productcompliance@molex.com</u>
Please visit the <u>Contact Us</u> section for any non-product compliance questions.

China ROHS Not Reviewed ELV Not Relevant

Search Parts in this Series

43249 Series

Mates With FCC 68 Plugs

Downloaded from Arrow.com.

Grounding to Panel Offset Panel Ground Tabs

Shielded Yes

Voltage - Maximum 150V AC (RMS)

Solder Process Data

Lead-freeProcess Capability WAVE

Material Info

Reference - Drawing Numbers

Packaging Specification PK-44050-004
Product Specification PSX-43249
Sales Drawing SDA-43249

This document was generated on 06/09/2016

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION