






A

B

C








D


A

B

C

D




dr	Rick Bian	2010/07/04	projection 	MM 	size	A4	scale	1.000
eng	Jeny Ren	2016/12/01			ecn no	ELX-DG-25425-1		
chr	-	-			rel level	Released		
appr	Nickor Zuo	2016/12/02	product family					
Amphenol FCI		title			dwg no			rev
		SMT DDRIII SOCKET ASS'Y			10109498			D
		DDRIII 240P RDIMM SOCKET(FOR CISCO)						
www.fci.com		cat. no.		*	Product - Customer Drw			sheet 3 of 4

A

B

C

D




SCALE 0.500
10109498-10***
CENTER SMT HOLDOWN TYPE




SCALE 0.500
10109498-11***
3 FORK LOCK TYPE



SCALE 0.500
10109498-12***
3 SMT HOLDOWN TYPE



SCALE 0.500
10109498-13***
3 SMT HOLDOWN AND 2 PLASTIC POST TYPE



SCALE 0.500
10109498-15***
3 PLASTIC POST TYPE

NOTES:

1. MATERIAL:
HOUSING: HIGH PERFORMANCE RESINS, GLASS FILLED UL94V-0 RATED.
EJECTOR: HIGH PERFORMANCE RESINS, GLASS FILLED UL94V-0 RATED.
TERMINAL: HIGH PERFORMANCE COPPER ALLOY
METAL CLIP: COPPER ALLOY.
2. FCI LOGO TO BE APPROXIMATELY LOCATED AS SHOWN ON PRINT.
3. PRODUCT SPECIFICATION: GS-12-486.
4. PACKAGING SPECIFICATION: GS-14-899.
5. RECOMMENDED STENCIL THICKNESS NO LESS THAN 0.15 mm.
6. FOR OPTIMUM PERFORMANCE, THE TIE BAR IS TO BE ON AN INTERNAL LAYER SO THAT THE REMNANT CANNOT CAUSE CONTACT DAMAGE.
7. THE DATE CODE IS SHOWN "MMDDYY*".
"*" MEANS PRODUCTION LINE.
8. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
9. THE HOUSING WILL WITH STAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN AN IR REFLOW SOLDERING APPLICATION.
10. PRODUCT APPLICATION SPEC GS-20-089.
11. THE HOLDOWN TYPES ARE OPTION FOR HOLDOWN OR FORKLOCK.



2

STYLE : MECHANICAL KEYING





1 : 1.5 VOLT. W/ CENTER KEY

HOLD DOWN TYPE

- 0 : CENTER HOLD DOWN, FORKLOCK AT BOTH END
1: 3 FORKLOCK TYPE
2: 3 SMT HOLDOWN TYPE
3: 3 SMT HOLDOWN AND 2 PLASTIC POST
5: 3 PLASTIC POST TYPE

PACKAGE AND MYLAR OPTION

- 0: SOFT TRAY WITHOUT MYLAR (OBSOLETE)
1: HARD TRAY WITH MYLAR
2: HARD TRAY WITHOUT MYLAR
3: SOFT TRAY WITH MYLAR (OBSOLETE)
4: CUSTOMIZED HARD TRAY WITH MYLAR
5: CUSTOMIZED HARD TRAY WITHOUT MYLAR

DETAIL N
SCALE 5.000DETAIL J
SCALE 5.000SECTION K-K
SCALE 5.000DETAIL M
SCALE 5.000


3


PLATING

CODE	CONTACT	SOLDERTAIL	UNDERPLATE	NOTE
1	10u" (0.25um) MIN. GOLD	100u" (2.54um) MIN. TIN-LEAD	50u" (1.27um) MIN. NICKEL OVERALL	CONTACT NON-LUBRICANT
2	15u" (0.38um) MIN. GOLD			
3	30u" (0.76um) MIN. GOLD			
4	GOLD FLASH			
5	10u" (0.25um) MIN. GOLD	100u" (2.54um) MIN. 100% MATT TIN	50u" (1.27um) MIN. NICKEL OVERALL	CONTACT LUBRICATED
6	15u" (0.38um) MIN. GOLD			
7	30u" (0.76um) MIN. GOLD			
8	GOLD FLASH			
1LF	10u" (0.25um) MIN. GOLD	100u" (2.54um) MIN. 100% MATT TIN	50u" (1.27um) MIN. NICKEL OVERALL	CONTACT NON-LUBRICANT
2LF	15u" (0.38um) MIN. GOLD			
3LF	30u" (0.76um) MIN. GOLD			
4LF	GOLD FLASH			
5LF	10u" (0.25um) MIN. GOLD	100u" (2.54um) MIN. 100% MATT TIN	50u" (1.27um) MIN. NICKEL OVERALL	CONTACT LUBRICATED
6LF	15u" (0.38um) MIN. GOLD			
7LF	30u" (0.76um) MIN. GOLD			
8LF	GOLD FLASH			

COLOR OF HOUSING AND EJECTOR

- 0 : BLACK HOUSING + IVORY EJECTOR
1 : BLACK HOUSING + BLACK EJECTOR
2 : BLACK HOUSING + BLUE(653C) EJECTOR
3 : BLACK HOUSING + YELLOW(1235C) EJECTOR

SCALE 0.500
WITH MYLAR TAPE (OPTIONAL)

dr	Rick Bian	2010/07/04	projection 	MM 	size	A4	scale	1.000	
eng	Jeny Ren	2016/12/01			ecn no				ELX-DG-25425-1
chr	-	-			rel level				Released
appr	Nickor Zuo	2016/12/02			product family				
Amphenol FCI		title			dwg no			rev	
		SMT DDRIII SOCKET ASS'Y			10109498			D	
		DDRIII 240P RDIMM SOCKET(FOR CISCO)							
www.fci.com		cat. no.		*	Product - Customer Drw			sheet 4 of 4	

2

3

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[FCI / Amphenol:](#)

[10109498-11113LF](#) [10109498-11104LF](#) [10109498-11124LF](#) [10109498-11134LF](#) [10109498-11114LF](#) [10109498-11213LF](#) [10109498-11203LF](#) [10109498-11223LF](#) [10109498-11233LF](#) [10109498-11423LF](#) [10109498-12123LF](#)