

Printed-circuit board connector - MVSTBW 2,5/ 2-ST RD - 1710547

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



The figure shows a 10-position

PCB connector, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 2, pitch: 5 mm, connection method: Screw connection with tension sleeve, color: red, contact surface: Tin

Your advantages

version of the product

- ✓ Allows connection of two conductors



Key Commercial Data

Packing unit	50 pc
GTIN	4 055626 161662
GTIN	4055626161662

Technical data

Dimensions

Length [1]	12.5 mm	
Width [w]	10 mm	
Height [h]	26 mm	
Pitch	5 mm	
Dimension a	5 mm	

General

Range of articles	MVSTBW 2,5/ST	
Number of positions	2	
Connection method	Screw connection with tension sleeve	
Insulating material group	I	
Rated voltage (III/2)	320 V	



Printed-circuit board connector - MVSTBW 2,5/ 2-ST RD - 1710547

Technical data

General

Nominal current I _N	12 A	
Nominal cross section	2.5 mm²	
Flammability rating according to UL 94	V0	

Standards and Regulations

Flammability rating according to UL 94	VO

Environmental Product Compliance

REACh SVHC	Lead 7439-92-1	
China RoHS	Environmentally Friendly Use Period = 50	
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"	

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC	EAC		B.01742
-----	-----	--	---------

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8

32825 Blomberg

Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1710547