

1530605

https://www.phoenixcontact.com/us/products/1530605

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector front mounting, 3-position, Socket, straight, M5, Front mounting, M5 x 0.5, Individual wires, cable length: 0.5 m, 0.14 mm $^2$ , TPE litz wire

#### Your advantages

- · Preassembled with litz wires for immediate use
- · Customer-specific assemblies and litz wire lengths available
- · Sealed on the litz wire side for optimum leak-tightness

#### Commercial data

Item number	1530605
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB21
Product key	ABQMBA
Catalog page	Page 32 (C-2-2019)
GTIN	4046356024402
Weight per piece (including packing)	6.8 g
Weight per piece (excluding packing)	6.8 g
Customs tariff number	85444290
Country of origin	DE



1530605

https://www.phoenixcontact.com/us/products/1530605

#### Technical data

#### Mounting

duct properties  Product type	Circular connectors (device side)
Number of positions	3
No. of cable outlets	1
Shielded	no
Coding	A
Thread type	M5

### Degree of pollution Material specifications

Flammability rating according to UL 94	НВ
Seal material	Viton
Contact material	CuSn
Contact surface material	Au
Contact carrier material	PA 6.6
Material for screw connection	Brass, nickel-plated

3

#### Electrical properties

Contact resistance	≤ 3 mΩ
Insulation resistance	≥ 100 MΩ
Nominal voltage $U_N$	48 V AC
	60 V DC
Nominal current I <sub>N</sub>	1 A
Test voltage	800 V

#### Connection data

#### Conductor connection

Connection method	Individual wires
Contact connection type	Socket
Conductor cross section	0.14 mm²

#### Connector

#### Connection 1

Head design	Socket
-------------	--------



1530605

https://www.phoenixcontact.com/us/products/1530605

Head cable outlet	straight
Head thread type	M5

#### Cable/line

Cable length	0.5 m
Cable type	TPE litz wire
Single wire, color	brown, blue, black
Cable cross section	0.14 mm²
Conductor structure signal line	18x 0.10 mm
AWG signal line	26
Material wire insulation	TPE
Ambient temperature (operation)	-25 °C 80 °C (cable, fixed installation)

#### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP67
	IP67
Ambient temperature (operation)	-25 °C 80 °C (cable, fixed installation)
	-25 °C 85 °C (Plug)

#### Standards and regulations

#### M5

Standard designation	M5 connector
Standards/specifications	IEC 61076-2-105




1530605

https://www.phoenixcontact.com/us/products/1530605

### Drawings

Schematic diagram



Pin assignment M5 socket, 3-pos., D-coded, view female side



1530605

https://www.phoenixcontact.com/us/products/1530605

#### Classifications

UNSPSC 21.0

#### **ECLASS**

27440102
27440116
27440116
EC002635

39121400



1530605

https://www.phoenixcontact.com/us/products/1530605

### Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	d36c1cfc-e9e0-4983-9ece-5e6142d122fe



1530605

https://www.phoenixcontact.com/us/products/1530605

#### Accessories

SACC-E-MU-M 5 - Flat nut

1535901

https://www.phoenixcontact.com/us/products/1535901

Flat nut, for threads M5 x 0.5



Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com