



660-021 (Plug) - 660-022 (Receptacle) Protective Covers MIL-C-83723 Series III Threaded

MIL-C-83723 Series III Threaded

660-021 M 14 S 5 -04
 Basic Part No. _____
 660-021 Plug
 660-022 Receptacle
 Finish (Table II) _____
 Shell Size (Table X) _____
 Ring or Eyelet Dash No.
 (Tables IV, V, VI, VII)
 Attachment Length (in inches)
 Attachment Type (Table III)



660-021 Plug Cover



660-022 Receptacle Cover

TABLE X: SHELL SIZE DIMENSIONS

Shell Size	E Thread Class 2A/2B	F Dia Max
08	9/16 - 24 UNEF	.776 (19.7)
10	11/16 - 24 UNEF	.906 (23.0)
12	7/8 - 20 UNEF	1.078 (27.4)
14	15/16 - 20 UNEF	1.141 (29.0)
16	1 1/16 - 18 UNEF	1.266 (32.2)
18	1 3/16 - 18 UNEF	1.375 (34.9)
20	1 5/16 - 18 UNEF	1.510 (38.4)
22	1 7/16 - 18 UNEF	1.625 (41.3)
24	1 9/16 - 18 UNEF	1.760 (44.7)

See inside back
 cover fold-out or
 page 14 for Table II.

Metric dimensions (mm)
 are indicated in paren-
 theses.

660-021 (Plug) - 660-022 (Receptacle)
Protective Covers
MIL-C-83723 Series III Threaded



66 & 78






TABLE III: ATTACHMENT

Sym	Attachment Type
D	Bead Chain, Cres., Passivate
F	Wire Rope, Nylon Jacket
G	Nylon Rope
H	Wire Rope, Fluoropolymer Jacket
N	No Attachment
R	Wire Rope, PVC Jacket
S	#8 Sash Chain, Cres., Passivate
T	Wire Rope, No Jacket
U	Wire Rope, Polyurethane Jacket with Terminal

TABLE IV: EYELET

Dash No.	K DIA.
	$\pm .010$ (0.3)
01	.140 (3.6)
02	.182 (4.6)
03	.191 (4.9)
04	.197 (5.0)
05	.167 (4.2)
06	.125 (3.2)
07	.218 (5.5)
09	.156 (4.0)
00	No Eyelet






TABLE V: SPLIT RING STYLE C

Dash No.	L Dia.	Dash No.	L Dia.
	$\pm .015$ (0.4)		$\pm .015$ (0.4)
50	.425 (10.8)	74	1.625 (41.3)
52	.485 (12.3)	76	1.750 (44.5)
54	.640 (16.3)	78	1.875 (47.6)
56	.750 (19.1)	80	1.980 (50.3)
58	.890 (22.6)	82	2.060 (52.3)
60	1.015 (25.8)	84	2.235 (56.8)
62	1.095 (27.8)	86	2.310 (58.7)
64	1.130 (28.7)	88	2.475 (62.9)
66	1.250 (31.8)	90	2.655 (67.4)
68	1.350 (34.3)	92	2.810 (71.4)
70	1.390 (35.3)	94	3.045 (77.3)
72	1.485 (37.7)		

TABLE VI: SOLID RING STYLE B

Dash No.	M Dia.	Dash No.	M Dia.
	$\pm .015$ (0.4)		$\pm .015$ (0.4)
08	.468 (11.9)	24	1.484 (37.7)
10	.593 (15.1)	25	1.577 (40.1)
12	.718 (18.2)	27	1.640 (41.7)
13	.765 (19.4)	28	1.687 (42.8)
14	.844 (21.4)	29	1.765 (44.8)
15	.890 (22.6)	30	1.890 (48.0)
16	.968 (24.6)	31	1.953 (49.6)
17	1.015 (25.8)	32	1.968 (50.0)
18	1.093 (27.8)	33	2.077 (52.8)
19	1.140 (29.0)	35	2.140 (54.4)
20	1.203 (30.6)	36	2.187 (55.5)
21	1.265 (32.1)	40	2.406 (61.1)
22	1.343 (34.1)	44	2.656 (67.5)
23	1.453 (36.9)	48	3.031 (77.0)
		118	.310 (7.9)

TABLE VII: SOLID RING STYLE A

Dash No.	N Dia.	Dash No.	N Dia.
	$\pm .015$ (0.4)		$\pm .015$ (0.4)
095	.312 (7.9)	109	1.266 (32.2)
100	.391 (9.9)	209	1.312 (33.3)
101	.516 (13.1)	110	1.391 (35.3)
102	.583 (14.8)	210	1.438 (36.5)
103	.641 (16.3)	111	1.521 (38.6)
104	.708 (18.0)	211	1.536 (39.0)
105	.766 (19.5)	112	1.641 (41.7)
205	.788 (20.0)	113	1.766 (44.9)
106	.896 (22.2)	213	1.812 (46.0)
206	.907 (23.0)	114	1.891 (48.0)
107	1.016 (25.8)	214	1.938 (49.2)
207	1.025 (26.0)	115	2.078 (52.8)
108	1.141 (29.0)	116	2.406 (61.1)
308	1.188 (30.2)	117	2.510 (63.8)
208	1.203 (30.6)		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Glenair:

[660-022M16R6-01](#) [660-021NF20H7-05](#) [660-021NF22H7-05](#) [660-022G20H4-04](#) [660-022NF20H7-05](#) [660-022NF22H7-05](#) [660-021G20T6-04](#) [660-021C14S6-06](#) [660-021D12D8-70](#) [660-021M08N](#) [660-021M12N](#) [660-021M16R6-17](#) [660-021M18R5-18](#) [660-021M18S5-04](#) [660-021M20S6-06](#) [660-021M20S8-06](#) [660-021M22S6-06](#) [660-021N08S7-05](#) [660-021N12G7-10](#) [660-021N20G7-10](#) [660-022B14R6-04](#) [660-022C14N](#) [660-022C24G6-01](#) [660-022C28F5-01](#) [660-022M08H6-118](#) [660-022M08N](#) [660-022M10T3-104](#) [660-022M12H3-06](#) [660-022M12N](#) [660-022M12S5-06](#) [660-022M14N-98](#) [660-022M14S5-01](#) [660-022M18H6-01](#) [660-022M18H6-04](#) [660-022M18N](#) [660-022M20S7-06](#) [660-022M20S8-06](#) [660-022M22S7-06](#) [660-022M22S8-06](#) [660-022M24H6-01](#) [660-022M24N](#) [660-022M28N](#) [660-022N08S7-05](#) [660-022N12S7-05](#) [660-022N18S5-05](#) [660-022NF12N-98](#) [660-022NF14S5-01](#) [660-022NF16F5-02](#) [660-022NF18N](#) [660-022NF18S5-05](#) [660-022NF22S5-01](#) [660-022Z108H5-06-59](#) [660-022Z108S3-01](#) [660-022Z110H5-04](#) [660-022Z112H4-07-49](#) [660-022Z116N](#) [660-022Z120R5-06](#) [660-022Z122N-122](#) [660-021C12S5-01](#) [660-021M12S5-09](#) [660-021M14S5-02](#) [660-021M16S5-107](#) [660-021N12S7-05](#) [660-022C12S5-01](#) [660-022M10H2-01](#) [660-022M24H3-01](#) [660-022M16N-59](#) [660-022B08S3-06](#) [660-022B24H4-07](#) [660-022M16H5-108](#) [660-022M16N](#) [660-022M20S9.5-06](#) [660-022Z118N](#) [660-022Z116H5-095](#) [660-022M14F6-58](#) [660-022Z120S5-06](#) [660-022M22N](#) [660-022M10H3-12](#) [660-022N14S7-05](#) [660-021N14S7-05](#) [660-022NF16F5-03](#)