


VCTU12V1K17P

Description


The VCTU12V1K17P transient voltage suppressor is designed to replace multilayer varistors (MLVs) in portable applications such as cell phones, notebook computers, and PDA's. They feature large cross-sectional area junctions for conducting high transient currents, offer desirable electrical characteristics for board level protection, such as fast response time, lower operating voltage, lower clamping voltage and no device degradation when compared to MLVs. The VCTU12V1K17P protects sensitive semiconductor components from damage or upset due to electrostatic discharge (ESD) and other voltage induced transient events. The VCTU12V1K17P is available in a DFN2×2-3L package with working voltages of 12 volt.



Pin configuration

Feature


- 4500W Peak pulse power per line ($t_p = 8/20\mu s$)
- DFN2×2-3L package
- Response time is typically $< 1\text{ ns}$
- Protect one I/O or power line
- Low clamping Voltage
- RoHS compliant
- Transient protection for data lines to IEC 61000-4-2(ESD) $\pm 30\text{KV}(\text{air}), \pm 30\text{KV}(\text{contact});$ IEC 61000-4-4 (EFT) 80A (5/50ns), IEC 61000-4-5 (Lightning) 200A (8/20us)



Circuit Diagram

Applications

- Cell phone handsets and accessories
- Personal digital assistants (PDA's)
- Notebooks, desktops, and servers
- Portable instrumentation
- Cordless phones
- Digital cameras
- Peripherals
- MP3 players




Marking (Top View)

Mechanical Characteristics

- Lead finish: 100% matte Sn(Tin)
- Mounting position: Any
- Qualified max reflow temperature: 260°C
- Device meets MSL 1 requirements
- Pure tin plating: $7 \sim 17\text{ }\mu\text{m}$
- Pin flatness: $\leq 3\text{ mil}$

Electronics Parameter

Symbol	Parameter
V_{RWM}	Peak Reverse Working Voltage
I_R	Reverse Leakage Current @ V_{RWM}
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current
I_{PP}	Maximum Reverse Peak Pulse Current
V_C	Clamping Voltage @ I_{PP}
P_{PP}	Peak Pulse Power
C_J	Junction Capacitance
I_F	Forward Current
V_F	Forward Voltage @ I_F








Electrical characteristics per line@25°C (unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Units
Peak Reverse Working Voltage	V_{RWM}				12	V
Breakdown Voltage	V_{BR}	$I_t = 1\text{mA}$	14	14.5		V
Reverse Leakage Current	I_R	$V_{RWM} = 12\text{V}$			1	μA
Maximum Reverse Peak Pulse	I_{PP}			200		A
Current Clamping Voltage	V_C	$I_{PP} = 40\text{A}$ $t_P = 8/20\mu\text{s}$		16	18	V
Clamping Voltage	V_C	$I_{PP} = 90\text{A}$ $t_P = 8/20\mu\text{s}$		18	20	V
Clamping Voltage	V_C	$I_{PP} = 140\text{A}$ $t_P = 8/20\mu\text{s}$		20.5	24	V
Clamping Voltage	V_C	$I_{PP} = 185\text{A}$ $t_P = 8/20\mu\text{s}$		25	30	V
Junction Capacitance	C_J	$V_R = 0\text{V}$ $f = 1\text{MHz}$		1000	1500	pF

Absolute maximum rating@25°C


Rating	Symbol	Value	Units
Peak Pulse Power ($t_P = 8/20\mu\text{s}$)	P_{PP}	4500	W
Lead Soldering Temperature	T_L	260 (10 sec)	$^{\circ}\text{C}$
Operating Temperature	T_J	-55 to 150	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-55 to 150	$^{\circ}\text{C}$

Typical Characteristics



Solder Reflow Recommendation

Peak Temp=257℃, Ramp Rate=0.802deg. °C/sec




PCB Design


For TVS diodes a low-ohmic and low-inductive path to chassis earth is absolutely mandatory in order to achieve good ESD protection. Novices in the area of ESD protection should take following suggestions to heart:

- Do not use stubs, but place the cathode of the TVS diode directly on the signal trace.
- Do not make false economies and save copper for the ground connection.
- Place via holes to ground as close as possible to the anode of the TVS diode.
- Use as many via holes as possible for the ground connection.
- Keep the length of via holes in mind! The longer the more inductance they will have.

Product dimension (DFN2×2-3L)



Dim	Millimeters	
	MIN	MAX
A	1.90	2.10
B	1.90	2.10
C	1.40	1.60
D	0.90	1.15
E	1.30BSC	
F	0.25	0.40
G	0.90	1.10
H	0.20	0.30
I	0.32	0.48
J	0.50	0.65
K	0.20	0.45
L	0.15	0.30



Recommended Soldering Pad

Unit:mm

Ordering information

Device	Package	Reel	Shipping
VCTU12V1K17P	DFN2×2-3L (Pb-Free)	7"	3000 / Tape & Reel

Important Notice and Disclaimer

Weforsemi reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

Weforsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Weforsemi assume any liability for application assistance or customer product design. Weforsemi does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Weforsemi .

Weforsemi products are not authorized for use as critical components in life support devices or systems without express written approval of Weforsemi .