# molex

Part Number: 314049532

Product Description: 2.54mm MX64 Sealed Crimp Housing, Single Row, TE Generation Y Terminal, Black, 8 Circuits, Key A, with CPA Lock, Terminals 4 and 7 Plugged

Series Number: 31404

Status: Active

**Product Category:** Connector Housings **Engineering Number: CVP314049532** 



#### **Documents & Resources**

#### **Drawings**

Drawing 314049532\_sd.pdf Packaging Design Drawing PK-31300-256-001.pdf

# 3D Models and Design Files

3D Model 314049532\_stp.zip

#### **Specifications**

Application Specification 314020000-000.pdf Application Specification AS-31402-000-001.pdf Product Specification PS-31404-001-1X8-001.pdf Test Summary 314040003-000.pdf Test Summary TS-31404-001-1X8-001.pdf

### **Product Environment Compliance**

#### Compliance

GADSL/IMDS	Compliant
China RoHS	•
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Contains Dodecamethylcyclohexasiloxane; Decamethylcyclopentasiloxane; Octamethylcyclotetrasiloxane per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

#### **Part Details**

#### General

Status	Active
Category	Connector Housings
Series	31404
Description	2.54mm MX64 Sealed Crimp Housing, Single Row, TE Generation Y Terminal, Black, 8 Circuits, Key A, with CPA Lock, Terminals 4 and 7 Plugged
Application	Power, Wire-to-Board
Product Family	MX64 Sealed Connectors
Product Name	MX64
UPC	191128776592

## Physical

Circuits (maximum)	8
Color - Resin	Black
Gender	Receptacle
Glow-Wire Capable	No
Keying to Mating Part	Yes
Lock to Mating Part	Yes
Material - Resin	PBT
Net Weight	9.356/g
Number of Rows	1

Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	2.54mm
Polarization	А
Polarized to Mating Part	Yes
Temperature Range - Operating	-40° to +125°C

## Mates With / Use With

# Mates with Part(s)

Description	Part Number
Mates With	Sensors, Other USCAR Interfaces

# Use with Part(s)

Description	Part Number
MX64 Wire Dress Covers	<u>31414</u>
Use With	TE Connectivity Generation Y 0.64mm

This document was generated on Sep 20, 2024