




**PennEngineering**  
**Corporate Headquarters – Danboro, PA**  
 5190 Old Easton Rd.  
 Danboro, PA 18916  
**Phone:** 215-766-8853  
**Toll-Free Phone:** 1-800-237-4736 (U.S. only)  
**Email:** [info@pemnet.com](mailto:info@pemnet.com)  
**Website:** [www.pemnet.com](http://www.pemnet.com)

## Part # SMTSO-632-4ET, ReelFast® Surface Mount Nuts and Spacers/Standoffs -

### Type SMTSO - Unified

Type SMTSO - ReelFast® surface mount nuts and standoffs are available threaded and unthreaded.

Packaged on 330 mm recyclable reels. Tape width is 24 mm. Supplied with polyimide patch for vacuum pick up. Reels conform to EIA-481.



### Specifications

<b>Thread Size</b>	.138-32 (#6-32)
<b>Thread Code</b>	632
<b>Length Code</b>	4
<b>L - Length ± .005</b>	.125 in
<b>Min. Sheet Thickness</b>	.060 in
<b>A Max.</b>	.060 in
<b>C Max.</b>	.208 in
<b>E ± .005</b>	.281 in
<b>øH - Hole Size in Sheet + .003 - .000</b>	.213 in
<b>øD - Min. Solder Pad</b>	.306 in
<b>Parts per Reel</b>	1000
<b>Pitch</b>	12 mm
<b>For Use in Sheet Hardness<sup>1</sup></b>	P.C. Board
<b>Thread Specification</b>	Internal, ASME B1.1, 2B



Fastener Material	Carbon Steel	
Standard Finish	Electro-Plated Tin, ASTM B545, Class A with Clear	Preservative Coating, Annealed
CAD Supplier	PennEngineering® (PEM®)	

<sup>1</sup> For use in P.C. Board