



- 

|                                                                                                                 |                        |                                  |            |                                            |                 |                             |                                  |                  |
|-----------------------------------------------------------------------------------------------------------------|------------------------|----------------------------------|------------|--------------------------------------------|-----------------|-----------------------------|----------------------------------|------------------|
| 2                                                                                                               | COPPER ALLOY           | CONTACT AREA:GOLD-PLATING 0.1 μm |            | 4                                          | PHOSPHOR BRONZE | UNDER PLATING:NICKEL 1.0 μm |                                  |                  |
|                                                                                                                 |                        | LEAD AREA:TIN-PLATING 1.0 μm     |            | 3                                          |                 | COPPER ALLOY                | CONTACT AREA:GOLD-PLATING 0.1 μm |                  |
|                                                                                                                 |                        | UNDER PLATING:NICKEL 1.0 μm      |            |                                            |                 |                             | LEAD AREA:TIN-PLATING 1.0 μm     |                  |
| 1                                                                                                               | POLYAMIDE              | BLACK UL94V-0                    |            |                                            |                 | UNDER PLATING:NICKEL 1.0 μm |                                  |                  |
| NO.                                                                                                             | MATERIAL               | FINISH . REMARKS                 |            | NO.                                        | MATERIAL        | FINISH . REMARKS            |                                  |                  |
| UNITS<br>mm                                                                                                     |                        | SCALE<br>2 : 1                   | COUNT<br>1 | DESCRIPTION OF REVISIONS<br>DIS-F-00006019 |                 | DESIGNED<br>AK. IWAHORI     | CHECKED<br>HT. YAMAGUCHI         | DATE<br>20200406 |
|  HIROSE ELECTRIC CO., LTD. | APPROVED : HS. OKAWA   |                                  | 20130313   | DRAWING NO.<br>EDC3-347271-00              |                 |                             |                                  |                  |
|                                                                                                                 | CHECKED : KI. HIROKAWA |                                  | 20130312   | PART NO.<br>FX30B-5P-3. 81DS               |                 |                             |                                  |                  |
|                                                                                                                 | DESIGNED : DK. AIMOTO  |                                  | 20130311   | CODE NO.<br>CL570-3403-5-00                |                 |                             |                                  |                  |
|                                                                                                                 | DRAWN : DK. AIMOTO     |                                  | 20130311   |                                            |                 |                             |                                  |                  |

Jul.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.  
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

