


NOTES:

- 1) 20 AWG, 1 CONDUCTOR W/41X36 TINNED COPPER STRANDING.
- 2) CONDUCTOR: RUBBER INSULATED
- 3) RATING: 60C/600 VOLTS MAX.
- 4) APPROVALS: NONE
- 5) CONDUCTOR O.D. : .173" (REF.)
- 6) PRODUCT IS ROHS & PROP 65 COMPLIANT
- 7) ALL DIMENSIONS IN INCHES UNLESS OTHERWISE NOTED.

1	FIRST ISSUE	2/26/08
REV	DESCRIPTION	DATE

	<input checked="" type="checkbox"/> Indianapolis, IN <input type="checkbox"/> Conover, N.C. <input type="checkbox"/> Freemont, CA <input type="checkbox"/> Aguascalientes, MX <input type="checkbox"/> Tijuana, Mexico <input type="checkbox"/> Hermosillo, MX <input type="checkbox"/> Clinton, AR <input type="checkbox"/> Kanata, Canada	Proprietary Notice:		MATERIAL: FINISH: JACKET: SMOOTH	SCALE: NOT TO SCALE	ECB: N/A	ITEM DESCRIPTION RETRACTILE TEST PROD - 1 PAIR	
	This document is the property of Volex Incorporated. The information contained herein is not to be disclosed to anyone without the express written consent of Volex Inc.	TOLERANCE UNLESS OTHERWISE SPECIFIED .XXX ± .005 .XX ± .02 .X ± .03 FRACT. ± 1/32" ANGULAR ± 1/2°	APPROVED STC		DRAWN BY STC	DATE: 2/26/08		
				PART NO. 6879				

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Volex:](#)

[6879](#)