




Power Double Lock

TE Internal #: 2005248-4
Housing, Receptacle, Wire-to-Wire, 2 Position, 3.96 mm [.156 in]
Centerline, Wire & Cable, UL 94V-0, Power Double Lock,
Rectangular Power Connectors

[View on TE.com >](#)

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: **Housing**
Connector & Housing Type: **Receptacle**
Connector System: **Wire-to-Wire**
Number of Positions: **2**
Centerline (Pitch): **3.96 mm [.156 in]**

Features

Product Type Features

Compatible With Discrete Wire Type	Stranded
Rectangular Power Connector Type	Housing
Connector & Housing Type	Receptacle
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	2
Number of Power Positions	0
Number of Signal Positions	0
Number of Rows	1

Electrical Characteristics

Operating Voltage	300 VAC
-------------------	---------

Contact Features



Contact Layout	Inline
Contact Retention Within Housing	Without
Contact Type	Tab

Termination Features

Termination Method to Wire & Cable	Crimp
------------------------------------	-------

Mechanical Attachment

Connector Mounting Type	Cable Mount (Free-Hanging)
-------------------------	----------------------------

Housing Features

Centerline (Pitch)	3.96 mm[.156 in]
Housing Color	Yellow
Housing Material	PA 66

Dimensions

Connector Height	9.94 mm
Product Length	26.1 mm

Usage Conditions

Operating Temperature Range	-30 – 65 °C[-22 – 149 °F]
-----------------------------	---------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

Compatible With Agency/Standards Products	CNR, USR
Compatible With Approved Standards Products	CSA/C22.2 No. 182.3-M1987, UL 1977
UL Flammability Rating	UL 94V-0
Glow Wire Rating	GWT 750°C (Without Flame)

Packaging Features

Packaging Quantity	300
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 177918-1
POWER DBL LOCK PLATE 2P



TE Part # CAT-P87024-R2435
Power Double Lock Receptacle



TE Part # CAT-P87024-T111
Power Double Lock Tab



TE Part # 2005247-4
PDL 2P PLUG 3.96(GWT) YEL



TE Part # 368590-1
PDL 2P DBL PLATE 3.96(GWT) NAT



TE Part # 2005247-9
PDL 2P PLUG 3.96(GWT) BLK

Also in the Series | Power Double Lock



Connector Contacts(24)

Connector Hardware(14)

Insertion & Extraction Tools(2)

Rectangular Power Connectors(283)

Customers Also Bought

TE Part #3-1971794-1
NEW GI CONN2.5 TPA 3P BLACK

TE Part #1827385-1
GIC 3.3 PLUG HOUSING 4P

TE Part #4-1971793-3
NEW GI CONN2.5 PLUG HSG 4P RED

TE Part #1376477-7
2.5MM PITCH SIGNAL MATE CONN

TE Part #2-2293382-5
AMP MONO-SHAPE TAB CONN 5P.
GW-V0

TE Part #2468539-1
110 PL EX HSG.,REC.,8MM,2P,
NATURAL

TE Part #4-1971794-2
GI2.5 TPA,4P

TE Part #1-2406852-9
9P MONOPLUG 2.5 W TUBE-B

TE Part #2-1969592-0
HSG,REC,FREE-HANGING,DUALROW,
EP2.5

TE Part #63659-4
MAG-MATE POST 27-23 016TPCUBR

Documents

Product Drawings
PDL 2P CAP 3.96 F/H(GWT) YEL
English

CAD Files
3D PDF
3D
Customer View Model
ENG_CVM_CVM_2005248-4_B.2d_dxf.zip



English

Customer View Model

[ENG_CVM_CVM_2005248-4_B.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2005248-4_B.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English