

Part Number: 1731090096

Product Description: FCT Standard-Density D-Sub Connector, Female, Straight, Solder Cup, Gold Plating, 500 Mating Cycles, #4-40 Clinch Nut, 25 Circuits, White Insulator

Series Number: 173109

Status: Active

Product Category: D-Sub Connectors **Engineering Number: FT25S0G1**



Documents & Resources

Drawings

1731090096_sd.pdf

3D Models and Design Files

1731090096_stp.zip

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|--|
| China RoHS | ® |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Contains Lead per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|--------------|---|
| Category | D-Sub Connectors |
| Series | 173109 |
| Description | FCT Standard-Density D-Sub Connector, Female, Straight, Solder Cup, Gold Plating, 500 Mating Cycles, #4-40 Clinch Nut, 25 Circuits, White Insulator |
| IP Rating | IP20 |
| Magnetic | Yes |
| Product Name | FCT Products |
| Туре | Standard Density |
| UPC | 889056485784 |

Electrical

| Current - Maximum per Contact | 7.5A |
|-------------------------------|------|
| Shielded | Yes |

Physical

| Circuits (Loaded) | 25 |
|--------------------------------|--------------|
| Circuits (maximum) | 25 |
| Color - Resin | White |
| Durability (mating cycles max) | 500 |
| Gender | Female |
| Material - Contact | Copper Alloy |
| Material - Resin | PBT |
| Material - Shell | Steel |
| Net Weight | 16.600/g |
| Number of Rows | 2 |

| Orientation | Straight |
|-------------------------------|------------------|
| Packaging Type | Carton |
| Panel Mount | Rear |
| Panel Mount Method | Thread-In |
| PCB Locator | No |
| PCB Retention | None |
| Pitch - Mating Interface | 2.84mm |
| Pitch - Termination Interface | 2.84mm |
| Plating - Contact | Gold over Nickel |
| Plating - Shell | Tin |
| Polarized to Mating Part | Yes |
| Ports | 1 |
| Temperature Range - Operating | -55° to +125°C |
| Termination Style | Solder Cup |
| Waterproof / Dustproof | No |
| Waterproof / Dustproof Type | IP20 |
| Wire Size (AWG) | 20 |

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|-------------|--|
| Mates With | FCT Standard-Density D-Sub, Size 3, 25 Position, Plug |

This document was generated on Oct 31, 2024