




- Notes
- ① The recommended tightening torque, REF. NO. ⑦: 2 to 2.5 N·m.
 - ② LOCTITE 263, HENKEL JAPAN or equivalent applies to prevent REF. NO. ① for loosening.
 - ③ One example of the rotation of REF. NO. ⑦ to REF. NO. ① is shown.
 - ④ The assembly this product applies to the manual ETAD-C0354-00

4	Brass	Gold plating 0.2μ min.			
3	Brass	Nickel under plating 2μ min.	7	Brass	Nickel plating
2	Polyamide	(Black) UL94V-0	6	Steel	Nickel plating
1	Zinc alloy	Matte finish nickel plated	5	Brass	Black Chromate Treatment (Trivalent Chrome)
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm					
		SCALE 2 : 1	COUNT ① 2	DESCRIPTION OF REVISIONS DIS-C-00016953	DESIGNED HT. ZENBA
				CHECKED EJ. KUNII	DATE 20240220
HRS HIROSE ELECTRIC CO., LTD.		APPROVED	•EJ. KUNII	20150929	DRAWING NO. EDC-010386-78-78
		CHECKED	•EJ. KUNII	20150929	PART NO. HR10A-10P-12P(78)
		DESIGNED	•TP. KOMATSU	20150929	CODE NO. CL0110-0401-7-78
		DRAWN	•TP. KOMATSU	20150929	① 1