



PRODUCTS

Chilisin provides inductor turnkey solutions for EMI, power and RF and a global technical team to support its customers. Chilisin has become one of the few inductor suppliers capable of providing a complete "one-stop shopping" experience.



Products Line

- Power Inductor
- Chip Inductor
- Bead
- Common Mode Choke

Product Search

Submit

LVF303010

Home > Products > Power Inductor > LVF303010

Part Number : LVF303010-2R2?-N

Structure	Closed Magnetic Circuit Type - Automatic Assembly
Inductance(?H)	2.2
Tolerance(±%)	20,30
Test Frequency	1MHz,200mV
RDC(ohm)	0.1
RDC Tolerance(±%)	30
Isat(A)Typ	1.50
Isat(A)Max	1.35
Irms(A)Typ	1.40
Irms(A)Max	1.26
Operating Temperature	－ 5 5℃～ 1 2 5℃(Including self - temperature rise)
L(mm)	3.0±0.20
W(mm)	3.0±0.20
T(mm)	1.02Max.

- 1.Isat for Inductance drop 30% from its value without current.
- 2.Irms for a 40℃ rise above 25℃ ambient.

P/N	LVF303010-2R2M-N
Part Numbering	
Dimensions	
Packing	
Recommended Pattern	
Electrical Characteristics Curve	

Back

