

# ME 22,5 OTU-MKDSO KMGY - Upper housing part



2278953

<https://www.phoenixcontact.com/us/products/2278953>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

DIN rail housing, Upper housing part for PCB terminal blocks with screw connection, width: 22.6 mm, height: 99 mm, depth: 45.85 mm, color: light gray (similar RAL 7035)



## Your advantages

- Tool-free mounting
- Available in overall widths from 12.5 mm ... 90 mm, modular extension is possible
- Flammability rating V0 in accordance with UL 94
- Variety of connection technology
- Can be mounted on the DIN rail
- With integrated or DIN-rail-mountable bus connector as an option

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 2278953             |
| Packing unit                         | 10 pc               |
| Minimum order quantity               | 10 pc               |
| Sales key                            | AC08                |
| Product key                          | ACHAAD              |
| Catalog page                         | Page 671 (C-1-2013) |
| GTIN                                 | 4046356328739       |
| Weight per piece (including packing) | 12.61 g             |
| Weight per piece (excluding packing) | 12.61 g             |
| Customs tariff number                | 85389099            |
| Country of origin                    | DE                  |

# ME 22,5 OTU-MKDSO KMGY - Upper housing part



2278953

<https://www.phoenixcontact.com/us/products/2278953>

## Technical data

### Notes

|               |   |
|---------------|---|
| Assembly note | Refer to the data sheet for the range in the download area. |
|---------------|---|


### Product properties

|                              |  |
|------------------------------|--|
| Product type                 | Upper housing part   |
| Housing type                 | DIN rail housing   |
| Housing series               | ME   |
| Product family               | ME 22,5..  |
| Max. number of positions     | 20 (pitch: 3.5 mm)<br>16 (pitch: 5 mm)                           |
| Type                         | Upper housing part for PCB terminal blocks with screw connection |
| Ventilation openings present | no   |

### Data management status

|                  |    |
|------------------|----|
| Article revision | 01 |
|------------------|----|

### Dimensions

|                                 |  |
|---------------------------------|--|
| Dimensional drawing             |  |
| Width                           | 22.6 mm  |
| Height                          | 99 mm  |
| Depth                           | 45.85 mm   |
| Depth from base support surface | 38.5 mm  |

### PCB design

|               |                   |
|---------------|-------------------|
| PCB thickness | 1.4 mm ... 1.8 mm |
|---------------|-------------------|

### Material specifications

|  |                       |
|--|-----------------------|
| Color (Housing)                        | light gray (RAL 7035) |
| Flammability rating according to UL 94 | V0                    |
| CTI according to IEC 60112             | 600                   |
| Housing material                       | Polyamide             |
| Surface characteristics                | untreated             |

### Environmental and real-life conditions

# ME 22,5 OTU-MKDSO KMGY - Upper housing part



2278953

<https://www.phoenixcontact.com/us/products/2278953>

## Vibration test

|                        |                             |
|------------------------|-----------------------------|
| Specification          | IEC 60068-2-6:2007-12       |
| Frequency              | 10 - 150 - 10 Hz            |
| Sweep speed            | 1 octave/min                |
| Amplitude              | 0.15 mm (10 Hz ... 58.1 Hz) |
| Acceleration           | 2g (58.1 Hz ... 150 Hz)     |
| Test duration per axis | 2.5 h                       |
| Test directions        | X-, Y- and Z-axis           |

## Glow-wire test

|                  |                        |
|------------------|------------------------|
| Specification    | IEC 60695-2-11:2014-02 |
| Temperature      | 850 °C                 |
| Time of exposure | 30 s                   |

## Thermal stability / ball thrust test

|               |                        |
|---------------|------------------------|
| Specification | IEC 60695-10-2:2014-02 |
| Temperature   | 125 °C                 |
| Test duration | 1 h                    |
| Force         | 20 N                   |

## Mechanical strength / tumbling barrel

|                |                     |
|----------------|---------------------|
| Specification  | IEC 60998-1:2002-12 |
| Height of fall | 50 cm               |
| Frequency      | 10                  |

## Shocks

|                                |                                   |
|--------------------------------|-----------------------------------|
| Specification                  | IEC 60068-2-27:2008-02            |
| Pulse shape                    | Half-sine                         |
| Acceleration                   | 15g                               |
| Shock duration                 | 11 ms                             |
| Number of shocks per direction | 3                                 |
| Test directions                | X-, Y- and Z-axis (pos. and neg.) |

## Degree of protection (IP code)

|               |   |
|---------------|---|
| Specification | IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08 |
|---------------|---|

## Ambient conditions

|   |  |
|---|--|
| Max. IP code to attain                  | IP20   |
| Ambient temperature (operation)         | -40 °C ... 105 °C (depending on power dissipation) |
| Ambient temperature (storage/transport) | -40 °C ... 55 °C                                   |
| Ambient temperature (assembly)          | -5 °C ... 100 °C                                   |
| Relative humidity (storage/transport)   | 80 %   |

## PCB data

|                       |      |
|-----------------------|------|
| Number of PCB holders | 1    |
| Type of PCB mount     | Slot |

# ME 22,5 OTU-MKDSO KMGY - Upper housing part



2278953

<https://www.phoenixcontact.com/us/products/2278953>

|                      |                   |
|----------------------|-------------------|
| Thickness of the PCB | 1.4 mm ... 1.8 mm |
|----------------------|-------------------|

## Mounting

|               |                                  |
|---------------|----------------------------------|
| Mounting type | Latching with lower housing part |
|---------------|----------------------------------|

## Packaging specifications

|                      |                     |
|----------------------|---------------------|
| Type of packaging    | packed in cardboard |
| Outer packaging type | Carton              |

# ME 22,5 OTU-MKDSO KMGY - Upper housing part


2278953

<https://www.phoenixcontact.com/us/products/2278953>



## Drawings

Dimensional drawing



Schematic figure for illustrating the item dimensions. The figure is not of the desired product. For further details, refer to the product drawings in the "Downloads" tab.

# ME 22,5 OTU-MKDSO KMGY - Upper housing part



2278953

<https://www.phoenixcontact.com/us/products/2278953>

## Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2278953>



**UL Recognized**

Approval ID: E240868

# ME 22,5 OTU-MKDSO KMGY - Upper housing part



2278953

<https://www.phoenixcontact.com/us/products/2278953>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27182702 |
| ECLASS-13.0 | 27190603 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002779 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 31261500 |
|-------------|----------|

# ME 22,5 OTU-MKDSO KMGY - Upper housing part



2278953

<https://www.phoenixcontact.com/us/products/2278953>

## Environmental product compliance

|   |  |
|---|--|
| EU RoHS                                 |  |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |  |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|   | No hazardous substances above the limits |
| EU REACH SVHC                           |  |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)