
Material name :

Evaluation data

Customer's product name :

TDK product name :

DC-DC converter
CC3-2412SF-E , CC3-2412SR-E

TDK-Lambda

TDK Corporation
Power Systems Business Group

DWG.No.	TRSC-1528-2
---------	-------------

Revised 2006/12/01

INDEX

1.Load regulation.....	P2
2.Line regulation.....	P2
3.Efficiency.....	P3
4.Switching frequency vs. output power.....	P3
5.Over current protection characteristics.....	P4
6.Output rise characteristics.....	P5
7.Output fall characteristics.....	P6
8.Dynamic load response characteristics.....	P7
9.Inrush current waveform.....	P7
10.Temperature distribution.....	P8

* The measurement has been done without external output capacitor.

(Product specification)

Product name	Input voltage(V)	Output voltage(V)	Output current(mA)	The maximum output power(W)	Ambient temperature(°C)
CC3-2412SF-E	18~36	12 ±3%	0~250	3	-40 ~ +85 *2
CC3-2412SR-E		15 ±3% *1	0~200		


*1 TRM and -Vout are short-circuited.

*2 At 50°C or more, output power derating is necessary.

Product name or model, title			
DC-DC converter CC3-2412SF-E , CC3-2412SR-E			
TDK CORPORATION	Name of drawing	Drawing No.	PAGE
	Evaluation data	TRSC-1528-2	1/ 8


1. Load regulation

Condition Ta : 25°C



2. Line regulation


Condition Ta : 25°C



TDK CORPORATION	Product name or model, title		
	DC-DC converter CC3-2412SF-E , CC3-241 2SR-E		
	Name of drawing	Drawing No.	PAGE
	Evaluation data	TRSC-1528-2	2/ 8


3. Efficiency

Condition Ta : 25°C



4. Switching frequency vs. output power


Condition Ta : 25°C



TDK CORPORATION	Product name or model, title		
	DC-DC converter CC3-2412SF-E , CC3-2412SR-E		
	Name of drawing	Drawing No.	PAGE
	Evaluation data	TRSC-1528-2	3/ 8

5. Over current protection characteristics



Condition Ta : 25℃



Product name or model, title			
DC-DC converter CC3-2412SF-E , CC3-241 2SR-E			
TDK CORPORATION	Name of drawing	Drawing No.	PAGE
	Evaluation data	TRSC-1528-2	4/ 8

6. Output rise characteristics



Condition Vin : 24V
Ta : 25°C



Product name or model, title			
DC-DC converter CC3-2412SF-E , CC3-2412SR-E			
TDK CORPORATION	Name of drawing	Drawing No.	PAGE
	Evaluation data	TRSC-1528-2	5/ 8

7. Output fall characteristics


Condition Vin : 24V
Ta : 25℃



Product name or model, title			
DC-DC converter CC3-2412SF-E , CC3-241 2SR-E			
TDK CORPORATION	Name of drawing	Drawing No.	PAGE
	Evaluation data	TRSC-1528-2	6/ 8


8. Dynamic load response characteristics

Condition Vin : 24V
Vout : 12V
Iout : 0% ⇔ 100%
Tr=Tf : 100 μs
f : 100Hz
Ta : 25℃



9. Inrush current waveform

Condition Vin : 36V
Iout : 100%
Ta : 25℃




Product name or model, title			
DC-DC converter CC3-2412SF-E , CC3-2412SR-E			
TDK CORPORATION	Name of drawing	Drawing No.	PAGE
	Evaluation data	TRSC-1528-2	7/ 8


10. Temperature distribution

Condition Vin : 24V
 Vout : 12V
 Iout : 100%
 Ta : 25℃
Wind velocity : 0m/s

Top View



Bottom View



(*) •This test was done on our evaluation board. (Glass epoxy substrate, Size:100x100x1.6mm)
•We measured the temperatures of parts without the case by using the thermography.
Therefore, it might be different a little from the actual temperature.

TDK CORPORATION	Product name or model, title		
	DC-DC converter CC3-2412SF-E , CC3-241 2SR-E		
	Name of drawing	Drawing No.	PAGE
	Evaluation data	TRSC-1528-2	8 / 8