



**International
Components
Corporation**

1337 Lincoln Avenue

Suite 5

Holbrook, NY 11741

Ph: (631) 952 - 9595 Fax:

E-mail: oemsales@icc107.com

SHIELDED LOW LEAKAGE OVAL SPEAKER

[Contact Us](#)



Product: SHIELDED LOW LEAKAGE OVAL SPEAKER

Description: These Speakers Are Available, On A Special Order Basis, In 4, 16, 32, 45 And 100 Ohms.

Part Number: S20X35VFS-2W

SPECIFICATIONS

FRAME DEPTH	38.0 mm
FRAME DIAMETER	50.0 x 90.0 mm
FREQUENCY RESPONSE	Fo ~ 18000
MATERIAL CONE/FRAME	PAPER / METAL
MEAN VALUE AT	0.6, 0.8, 1.0, 1.2KHz
MEASURED AT	1.0 W @ 0.5M
OUTPUT SOUND PRESSURE LEVEL (S.P.L)	86 ± 3 dB
RATED POWER WATTS Nom/Max	2.00 / 5.00
RESONANT FREQUENCY HZ WITOUT BAFFLE	240 ± 20%
ROHS COMPLAINT	YES
VOICE COIL IMPEDANCE	8 ± 15% @1.0KHz

1337 Lincoln Avenue Suite 5 Holbrook, NY 11741 , Telephone: (631) 952 - 9595, Fax: