

Jul.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD																		
RATING	OPERATING TEMPERATURE RANGE	-35°C TO +85°C (NOTES 1)	STORAGE TEMPERATURE RANGE	-10°C TO + 60°C														
	VOLTAGE	50V AC	APPLICABLE CONNECTOR	DF17#(**)-*DS-0. 5V (57)														
	CURRENT	0. 3A																
SPECIFICATIONS																		
ITEM		TEST METHOD	REQUIREMENTS	QT	AT													
CONSTRUCTION																		
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X													
MARKING		CONFIRMED VISUALLY.		X	X													
ELECTRIC CHARACTERISTICS																		
CONTACT RESISTANCE		100m A (DC OR 1000 Hz).	60mΩ MAX.	X	—													
INSULATION RESISTANCE		100V DC.	500MΩ MIN.	X	—													
VOLTAGE PROOF		150V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	—													
MECHANICAL CHARACTERISTICS																		
INSERTION AND WITHDRAWAL FORCES		MEASURED BY APPLICABLE CONNECTOR. 	<table><tr><td rowspan="6">PIN COUNT</td><td>INSERTION FORCE (N)MAX</td><td>WITHDRAWAL FORCE (N)MIN</td></tr><tr><td>30</td><td>3.0</td></tr><tr><td>40</td><td>4.0</td></tr><tr><td>50</td><td>5.0</td></tr><tr><td>60</td><td>6.0</td></tr><tr><td>80</td><td>8.0</td></tr></table>	PIN COUNT	INSERTION FORCE (N)MAX	WITHDRAWAL FORCE (N)MIN	30	3.0	40	4.0	50	5.0	60	6.0	80	8.0	X	—
PIN COUNT	INSERTION FORCE (N)MAX	WITHDRAWAL FORCE (N)MIN																
	30	3.0																
	40	4.0																
	50	5.0																
	60	6.0																
	80	8.0																
MECHANICAL OPERATION		50TIMES INSERTIONS AND EXTRACTIONS.	① CONTACT RESISTANCE: 60mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—													
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—													
SHOCK		490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—													
ENVIRONMENTAL CHARACTERISTICS																		
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55→ 5 TO 35→ 85→ 5 TO 35°C TIME 30→10 TO 15→ 30→10TO15min UNDER 5 CYCLES.	① CONTACT RESISTANCE: 60mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—													
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.	① CONTACT RESISTANCE: 60mΩ MAX. ② INSULATION RESISTANCE: 250 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—													
CORROSION SALT MIST		EXPOSED IN 5% SALT WATER SPRAY FOR 48 h.	① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.	x	—													
SULPHUR DIOXIDE		EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD:JEIDA-39)	① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.	x	—													
HEAT RESISTANCE OF SOLDERING		【RECOMMENDED TEMPERATURE PROFILE】 《SOLDERING AREA》 MAX250°C, 220°C FOR 60 SECONDS MAX. 《PREHEATING AREA》 150 TO 180°C 120 SECONDS. MAXIMUM TWICE ACTION IS ALLOWED UNDER THE SAME CONDITION. 【RECOMMENDED MANUAL SOLDELING CONDITION】 SOLDERING IRON TEMPERATURE 350°C SOLDERING TIME : WITHIN 3 SECONDS.	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.	x	—													
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE													
	1	DIS-H-00003088	SH. HOSODA	TS. MIYAZAKI	17. 09. 29													
REMARKS			APPROVED	MO. NAKAMURA	05. 05. 20													
NOTE1:INCLUDING THE TEMPERATURE RISE BY CURRENT.			CHECKED	TS. MIYAZAKI	05. 05. 19													
UNLESS OTHERWISE SPECIFIED,REFER TO JIS C 0806.			DESIGNED	YH. MICHIDA	05. 05. 19													
			DRAWN	YH. MICHIDA	05. 05. 19													
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC4-162140-06														
	SPECIFICATION SHEET		PART NO.	DF17A (4. 0) -*DP-0. 5V (57)														
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL683	 1/1													