

Type 2 surge protection replacement module - VAL-SQ SI 40-2S-240 - 2800006

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid
(<http://phoenixcontact.com/download>)



Surge protection device for 2-phase, 240 V applications with separate Gnd-N. Provides 40 kA protection per phase. Compact, NEMA 4X enclosure installs in limited space.

Product Description

40 kA Type 2 surge protective device for systems up to 240 V with separate GND-N

Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 347495
GTIN	4046356347495

Technical data

Dimensions

Height	91.4 mm
Width	76.2 mm
Depth	69.3 mm

Ambient conditions

Degree of protection	IP66 / NEMA 4X
Ambient temperature (operation)	-40 °C ... 70 °C
Altitude	3658 m

General

IEC power supply system	TN-S
NEMA power supply system	2-phase, 240 V with separate Gnd-N
Housing material	Non-metallic
Mounting type	1/2" NPT male
Type	MOV
Surge protection fault message	optical

Protective circuit

IEC test classification	I
-------------------------	---

Type 2 surge protection replacement module - VAL-SQ SI 40-2S-240 - 2800006

Technical data

Protective circuit

Maximum continuous operating voltage U_c	240 V
--	-------

Connection, protective circuit

Connection method	#10 AWG/5.26 mm ² wires (24 in./61 cm long)
-------------------	--

Standards and Regulations


Standards/regulations	UL 1449 2 nd edition, February 2007
	UL 1283
	IEEE C62.41
	IEEE C62.45

NEMA / UL data

UL type	type 2
Maximum Surge Current per Phase	40 kA
Short-circuit current rating (SCCR)	10 kA

Drawings

Circuit diagram



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[2800006](#)