



PCB LAYOUT
(BOTTOM VIEW)

规格说明: Specifications:

电气特性: Electrical:

- 额定电流: Current Rating
1.5A/contact terminal
- 额定电压: Voltage Rating
30V DC
- 接触电阻: Contact Resistance
30 milliohms MAX
- 耐压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
- 绝缘电阻: Insulation Resistance:
1000MEGA ohms MIN

物理性能: Mechanical:

- 插拔力: Connector Mate and Unmate Force
Mate force: 3.57kgf(MAX)
Unmate force: 1.02kgf(MIN)
- 端子保持力: Terminal Retention
1.2kgf(MIN)

原材料: Material:

- 塑胶: Housing:
Hing Temperature Tnermaplastics,
UL 94V-0 PBT White/Black
- 端子: Contact: Copper Alloy C2680
- 外壳: Shell: Copper Alloy C2680/SPCC

电镀: Finish:

- 端子: Contact: Plated Gold in Mating Area,
Tin On Solder Tails
- 外壳: Shell:
Nickel Plating

 深圳市万骏达电子有限公司 http://www.wanjunda.com		图号 (DWG NO)	单位 (UNIT) : MM
品名 (ITEM NO)	AF14mm侧插弯脚卷边 0型脚	版本 (REV)	比例 (SCALE) 1:1
料号 (PART NO)	USB2.0-AF-CCS-JB-14.0	日期 (DATE)	 未注公差 TOLERANCE UNSPECIFIED X.X ±0.30 X.XX ±0.20 X.XXX ±0.10 X° ±5° X.X° ±2°
型号 (MODEL NO)		设计 (DESIGN)	
		审核 (CHECKED)	
		核准 (APPROVED)	