





ROHS compliant



NOTES:

1.Specification:

- 1>. Operation force: 500gf Max.
- 2>. Operation Temperature: -30℃ to +85℃.
- 3>. Storage Temperature: -40℃ to +85℃.
- 4>. Mechanical Life: 3000 cycles operations.
- 5>. Resistance to Soldering: 260±5℃ for 3-5 Seconds.

2.PLATING:


- 1>. GOLD flash 1u" (min) SOLDER TAIL,
- 3u" GOLD PLATING ON THE CONTACT AREA.

3.ELECTRICAL:

- 1>. Non-switch Rating: 100mA at 50V DC.
- 2>. Switching Rating: 25mA at 24V DC.
- 3>. Contact Resistance: Initial 50mΩ Max.
Contact Resistance: After life 100mΩ Max.
- 4>. Insulation Resistance: 1000MΩ Min at 500VDC.
- 5>. Dielectric Strength: 500V AC for 60seconds.
- 6>. Switch Capacitance: 5PF Max at 1MHZ.

4.PART NUMBER DESCRIPTION:

DSPV XX L H G E T



5.PACKING: 44pcs/Tube, 1760pcs/Box.

REV.	ECN NO.	DRAWN	DATE

东莞市康深电子科技有限公司
Kongshen Electronics technology co., LTD.

Drawing	dengk	Date	2018.03.25	LINER		ANGLES		PRODUCT Family	DSPV Series Pitch 2.54mm
Check	zhong	Scale	4:1					PRAT NO.	DSPV04LHGET
Approved		Unit	MM					FILE NO.	KE-DSPV-004-A
Size	A4	Rev.	A					PROJECTION	