

TE Internal #: 2081898-1

SMA RF Interface, Jack, 50 ohm, .047 Semi-Rigid or Flex, Screw, 0 –

27 GHz Operating Frequency, Cable-to-Cable, 1 Position, Wire &

Cable

View on TE.com >




Connectors > RF Connectors > Coax Connectors











RF Interface: SMA

RF Connector Style: Jack

Impedance: 50Ω

Compatible With RF Cable Type: .047 Semi-Rigid or Flex

RF Connector Coupling Mechanism: Screw

Features

Product Type Features

r roduct Type reatures	
RF Interface	SMA
RF Connector Style	Jack
Compatible With RF Cable Type	.047 Semi-Rigid or Flex
Connector System	Cable-to-Cable
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	1
Number of Coaxial Contacts	1
Electrical Characteristics	

Body Features

Impedance

Cable Connector Orientation	Straight
Body Material	Stainless Steel

50 Ω



Body Material Finish	Passivated
Contact Features	
RF Connector Center Contact Plating Material	Gold
RF Connector Center Contact Material	Beryllium Copper
Mechanical Attachment	
RF Connector Coupling Mechanism	Screw
RF Contact Captivation Method	Mechanical
Detent	Without
Usage Conditions	
Operating Temperature Range	-55 – 165 °C[-55 – 165 °F]
Operation/Application	
Circuit Application	Signal
Operating Frequency	0 – 27 GHz
Packaging Features	
Packaging Method	Bag & Box
Other	
Dielectric Material	PTFE

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Pb (4.75% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



Documents

Product Drawings

EP-SMA, JACK, STRAIGHT, 27GHZ, 047 CABLE

English

CAD Files

3D PDF



3D

Customer View Model

ENG_CVM_CVM_2081898-1_1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2081898-1_1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2081898-1_1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Product Specification

English