


6		5		
ITEM	PART#	DESCRIPTION	QTY	UOM
A	512160400	2.0 WtB Rec Hsg 4Ckt	1	PC
B	593708000	2.0 WtB Crimp Rec Chn	4	PC
C	----	WHITE PART ID LABEL	1	PC

PART NUMBER	TITLE	L1	L2(REF)
2244831040	MicroTPA 2.0 R-S 4ckt 50mm disc Sn	50±5	15
2244831041	MicroTPA 2.0 R-S 4ckt 100mm disc Sn	100±5	15
2244831042	MicroTPA 2.0 R-S 4ckt 150mm disc Sn	150±5	15
2244831043	MicroTPA 2.0 R-S 4ckt 300mm disc Sn	300±5	15
2244831044	MicroTPA 2.0 R-S 4ckt 600mm disc Sn	600±5	15

2		1	
FROM	TO	DESCRIPTION	COLOUR
A1	--	1X22AWG DISC SR-PVC BK UL10002	BLACK
A2	--	1X22AWG DISC SR-PVC BK UL10002	BLACK
A3	--	1X22AWG DISC SR-PVC BK UL10002	BLACK
A4	--	1X22AWG DISC SR-PVC BK UL10002	BLACK



NOTES:

1. CABLE ASSEMBLY MUST PASS 100% CONTINUITY AND POLARITY TEST.
2. CONNECTOR VIEW SHOWN FROM MATING SIDE.
- 3.LABEL TEXT MUST BE 2 MM MAX. IN HEIGHT WITH ARIAL FONT.
- 4.LABEL MUST BE WRAPPED IN FLAG TYPE ON A SINGLE CABLE.
- 5.TINNING SHOULD BE DONE WITH LEAD FREE SOLDER BAR ONLY.
- 6.FREE ENDS MUST BE STRIPPED,TWISTED & TINNED.THE LENGTH OF TINNING IS 5±1MM.TINNING DIA MUST BE 0.90 MM MAX.

REVISION				
DATE	REV	DESCRIPTION	CHANGER	
2023/01/04	A	INITIAL RELEASE	THANUB	
RELEASE STATUS	P1	RELEASE DATE	2023/02/08	09:35:33

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	
	DIMENSION UNITS	SCALE
	mm	NTS
	GENERAL TOLERANCES (UNLESS SPECIFIED)	
	ANGULAR TOL	± °
DIVISIONAL SYMBOLS	4 PLACES	±
	3 PLACES	±
	2 PLACES	±
	1 PLACE	±
	0 PLACES	±
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION
		DRAWING
		SERIES
		MATERIAL NUMBER
		CUSTOMER
		SHEET NUMBER

MOLEX P/N
MOLEX
BATCH WK/YR

DETAIL A