

# COAXIAL CONNECTOR, MMCX, 50 Ohm, Straight bulkhead cable jack (female)

24\_MMCX-50-1-6/111\_O

## Properties

- Very small size
- Easy to connect and disconnect
- Wide range of board connectors and cable connectors available



Product configuration		
Interface type	Gender	Standard
MMCX	jack	HUBER+SUHNER-MMCX

Interface and material data		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	
Fastening nut	Brass	Gold Plating (without Nickel underplating)
Washer	Bronze	Gold Plating (without Nickel underplating)
Crimp ferrule	Brass	Gold Plating (without Nickel underplating)

Electrical data	
Impedance	50 Ω
Interface frequency	6 GHz

Mechanical data	
Weight	0.0012 kg
Mating cycles	500
Cable entry centre contact	crimped
Cable entry outer contact	crimped

Environmental data	
Operation temperature	-55 °C ... 155 °C

COAXIAL CONNECTOR, MMCX, 50 Ohm, Straight bulkhead cable jack (female)  
24\_MMCX-50-1-6/111\_O

Ordering Information Table		
Item number	Item description	Packaging type
22652041	24_MMCX-50-1-6/111_OE	Single
Suitable cables		
Cable group	U1 - 1 mm / 50 Ohm	
Suitable cables	ENVIROFLEX_178	
	RG_196_A/U	
	RG_178_B/U	
Additional Information		
Only as assembly	No	

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.  
DOCUMENT PIM-P2632 / Date of publication: 01.12.2023 / uncontrolled copy