

A/F无后盖无边直脚/DIP (5.5)

目錄
MAPX设变内容
MODIFICATION日期
DATE

NOTES:

Housing: Thermoplastics,UL94V-0

Contact: Copper Alloy

Shell: Copper Alloy/Steel

Voltage Current Rating:1.5 AMP. 30V AC

Insulation Resistance:1000M Ω Min.Contact Resistance: 30 M Ω Max.

Dielectric Withstanding Voltage:500W AC

Temperature Range:-35°C to +85°C

Insulator color: Black/White

Plastic material:PBT/LCP/Others

Shell finish:Nickel plated/Tin-Lead plated

Mechanical:

Mating Force: 3.5KG MAX

Unmating Force:0.7 KG MIN.

Contact finish:




01: Selective Gold Flash

02: Selective Gold 3U"

03: Selective Gold 5U"

04: Selective Gold 15U"

05: Selective Gold 30U"



RBCOMMENDBD P.C.B PATTBRN LAYD UT

备注：侧弹分为外弹与内弹

产品图
PRODUCT CHART DWG公差一览表
TOLERANCE UNLESS OTHERWISE

X.	±0.35	X'.	±5"
.X	±0.25	.X'	±2"
.XX	±0.15	.XX'	±1"
.XXX	±0.10	.XXX'	±0.5"

深圳市精拓金电子有限公司

单位 UNITS	MM	制图 DRAWING	Z-Y-B	产品料号 PRODUCT PART NO.	903-242A1027S10200
比例 SCALE	1:1	审核 CHKD	雷永键	产品名称 PRODUCT NO.	AF90度无后盖直脚无边内弹改模后 铜壳一型5.25PBT白胶 高5.7
日期 DATE	2014/05/24	核准 APPD	雷永键	角法 VIEW	
				版本 VER	A0