



+ RELAYS, CONTACTORS & SWITCHES  
SLIDE SWITCHES



✓ Active

TE CONNECTIVITY (TE)  
MHS22204=DPDT SL SW VERT AG  
[Alcoswitch](#) | [MHS](#)

1825289-1  
TE Internal Number: 1825289-1  
Alias ID: MSH22204

- [EU RoHS Compliant](#)
- [EU ELV Compliant](#)
- Configuration (Pole-Throw)** Double Pole - Double Throw
- Mounting Angle** Vertical
- Contact Base Material** Copper Alloy
- Number of Actuators** Single
- Number of Positions** 2

↓ **PRODUCT DRAWING**  
English

DOCUMENTATION

Product Drawings  
**SLIDE SWITCH, MHS SERIES, DOUBLE POLE, VERTICAL**  
PDF  
English

Catalog Pages/Data Sheets  
**SWITCHES\_CORE\_PROGRAM\_CATALOG**  
PDF  
English

FEATURES

Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

- Terminal Configuration** Standard
- Switch Style** Low Profile
- Actuator Style** Lever
- Product Type** Switch
- Switch Type** Slide
- Grade** Instrumentation
- Threaded Case** Without

Configuration Features

- Configuration (Pole-Throw)** Double Pole - Double Throw
- Number of Actuators** Single
- Number of Positions** 2
- Operating Function** On None On
- Terminals Connected** 5-4, 2-1

Body Features

- Actuator Color** Black
- Actuator Material** Thermoplastic
- Actuator Travel** 4 mm [ .158 in ]

Contact Features

- Contact Base Material** Copper Alloy
- Contact Current Rating (A)** .3
- Contact Plating** Silver

Termination Features

- Termination Type** PC

Mechanical Attachment

- Mounting Angle** Vertical
- Mounting Type** Through Hole
- PCB Mount Retention Type** Guide Posts
- PCB Mount Retention** With

Dimensions

- Length** 15 mm [ .5906 in ]
- Width** 6.2 mm [ .2441 in ]
- Actuator Length** 4.5 mm [ .18 in ]
- PCB Tail Length** 3.51 mm [ .138 in ]

Industry Standards

- UL Flammability Rating** UL 94-HB

Packaging Features

- Packaging Method** Tray



Statement of Compliance

**Statement of Compliance**

PDF

