




PCB LAYOUT

- SPECIFICATIONS
- 1、Current Rating: 3A AC, DC
 - 2、Voltage Rating: 300V AC, DC
 - 3、Temperature Range: -25°C~+85°C
 - 4、Contact Resistance: 20mΩ Max
 - 5、Insulation Resistance: 1000MΩ Min
 - 6、Withstanding Voltage: 800V AC/minute
 - 7、Material: Wafer Nylon6T, UL94V-0
PIN Brass Tin-plated
Solder tab Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
A2021-1-02AWB	2.00	8.00
A2021-1-03AWB	4.00	10.00
A2021-1-04AWB	6.00	12.00
A2021-1-05AWB	8.00	14.00
A2021-1-06AWB	10.00	16.00
A2021-1-07AWB	12.00	18.00
A2021-1-08AWB	14.00	20.00
A2021-1-09AWB	16.00	22.00
A2021-1-10AWB	18.00	24.00
A2021-1-11AWB	20.00	26.00
A2021-1-12AWB	22.00	28.00
A2021-1-15AWB	28.00	34.00



单位 UNIT	mm	深圳市泰华电子有限公司 TaiHua Electronics Co., Ltd
比例 SCALE	1:1	版本号: 00
核准: APPROVED BY	X * ±	产品名称 Production name
审核: CHECKED BY	X * ±	产品型号 Product No
制图: DRAWN BY	X * ±	客户编号 Client No
封文日期: DATE	2022.9.5	日期: