



Polyester braided sleeving for reduction of vibration noise

Helagaine HEGSAS

Helagaine HEGSAS is used primarily in the automotive sector and wherever vibration noise must be reduced. Helagaine HEGSAS can be supplied in pre-cut lengths on request.

Features and Benefits

- Superior noise reduction
- Made of sturdy polyester
- Highly flexible
- Expansion rate of 3:1
- Easy to apply over irregular shapes due
- High surface coverage
- Excellent abrasion resistance



Helagaine HEGSAS braided sleeving.

MATERIAL	Polyester (PET)
Operating Temperature	-50 °C to +150 °C, intermittent +200 °C
Melting Point	+250 °C
Flammability	FMVSS 302

HF ✓

RoHS ✓



To prevent fraying, the sleeve can be cut with the hot cutting tool HSG0. See page 533.

TYPE	Bundle Ø min.	Bundle Ø max.	Colour	Reel Length	Article-No.
HEGSAS04	2.0	8.0	Black (BK)	200 m	170-60401
HEGSAS06	4.0	11.0	Black (BK)	200 m	170-60600
HEGSAS09	6.0	16.0	Black (BK)	100 m	170-60900
HEGSAS12	8.0	20.0	Black (BK)	100 m	170-61200
HEGSAS15	10.0	24.0	Black (BK)	50 m	170-61500
HEGSAS20	13.0	30.0	Black (BK)	50 m	170-62000
HEGSAS30	20.0	40.0	Black (BK)	25 m	170-63000
HEGSAS40	30.0	50.0	Black (BK)	25 m	170-64000

All dimensions in mm. Subject to technical changes.

Colour grey available on request. Cuts in any lengths. Minimum Order Quantity (MOQ) may differ from package content.