

Feed-through header - MSTBV 2,5/ 2-G OG - 1709974

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

PCB headers, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 2, pitch: 5 mm, color: orange, contact surface: Tin, mounting: Soldering



The figure shows a 10-position version of the product

Your advantages

- Maximum flexibility when it comes to device design one header for connectors with different connection technologies
- ☑ Well-known mounting principle allows worldwide use
- ✓ Vertical connection enables multi-row arrangement on the PCB
- Items that can be aligned in various pitches support flexible and space-saving PCB assembly



Key Commercial Data

Packing unit	250 pc
GTIN	4 055626 145457
GTIN	4055626145457

Technical data

Dimensions

Pitch	5 mm
Length of the solder pin	3.9 mm
Pin dimensions	1 x 1 mm

General

Range of articles	MSTBV 2,5/G
Insulating material group	I
Rated voltage (III/2)	320 V
Nominal current I _N	12 A
Flammability rating according to UL 94	V0
Color	orange



Feed-through header - MSTBV 2,5/ 2-G OG - 1709974

Technical data

General	
Number of positions	2
Standards and Regulations	
Flammability rating according to UL 94	V0
Environmental Product Compliance	
China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values
Approvals	
Approvals	
EAC	
Ex Approvals	
Approval details	
EAC [H[B.01742

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact: 1709974