



PRODUCT SELECTOR

PRODUCT TYPE

Search All



POSITIONS

Search All



IP RATING

Search All



AMPERAGE

Search All



HOUSING MATERIAL

Search All



PRODUCT LINE

Search All



VOLTAGE

Search All



RESET

SEARCH

Home > Our Product Lines > C091 Connectors > C091 D+ > 5 Position Cable Connectors > C091 11H005 002 4 - M16 Male cable connector with internal strain relief and metal locking ring. 5 contacts, 8-10.5mm cable diameter.



C091 11H005 002 4 - M16 MALE CABLE CONNECTOR WITH INTERNAL STRAIN RELIEF AND METAL LOCKING RING. 5 CONTACTS, 8-10.5MM CABLE DIAMETER.

PART NUMBER: C09111H0050024

[DATASHEET:](#) View / Download

SPECIFICATIONS:

Contacts: 5**Cable Diameter:** 8 - 10.5mm**Current Rating:** 7A**Termination:** Crimp**Locking:** Screw**Insert:** Thermoplastic**Version:** Straight; metal**Wire Gauge:** 0.09 - 1.0mm² (28-18 AWG)**Housing:** Zinc die cast, nickel plated**Protection:** IP 69K / IP 68**Insertion/Withdrawal Force:** 35 N**Insulation Resistance:** > 10(10) Ω**Rated Voltage IEC 60664-1:** 300V**Rated Voltage per UL 1977:** 250V**Rated Impulse Withstanding Voltage IEC 60664-1:** 1500V**Contact Resistance:** < 5m ohms**Sealing Material:** Chloroprene**Operating Temperature:** -40°C to +100°C**Mating Part(s):** C09111D00500024,C09111N00500002,C09111G00500002**Size:** M16

QUANTITY

1



REQUEST A QUOTE



Sign Up to see what your friends like.



Sign Up to see what your friends like.

DESCRIPTION

Male cable connector with internal strain relief and metal locking ring. 5 contacts, 8-10.5mm cable diameter. Complete EMI shielding in the fully mated and locked position (EMI security). Screw locking according to IEC 61076-2-106. Fully intermateable with C091D connectors. Contacts sold separately.

RELATED ITEMS



C091 11N005 000 2 - M16 Front mounting female metal receptacle with O-ring seal and ring nut mount. 5 contacts. Contacts sold separately.



C09111G0050002 Rear mounting female metal receptacle with O-ring seal and ring nut mount (hex nut available upon request). 5 contacts.



C091 11D005 002 4 - M16 Female cable connector with internal strain relief and metal locking ring. 5 contacts, 8-10.5mm cable diameter.

BROWSE SIMILAR ITEMS

- > Market Applications > Heavy Equipment > Agriculture > C091 Connectors > C091 D+ > 5 Position Cable Connectors
- > Market Applications > Heavy Equipment > Construction > C091 Connectors > C091 D+ > 5 Position Cable Connectors
- > Market Applications > Heavy Equipment > Transportation > C091 Connectors > C091 D+ > 5 Position Cable Connectors
- > Market Applications > Heavy Equipment > Off Road Recreation > C091 Connectors > C091 D+ > 5 Position Cable Connectors
- > Market Applications > Heavy Equipment > Industrial > C091 Connectors > C091 D+ > 5 Position Cable Connectors
- > Market Applications > Automation > Conveyors > C091 Connectors > C091 D+ > 5 Position Cable Connectors
- > Market Applications > Automation > Packaging Machinery > C091 Connectors > C091 D+ > 5 Position Cable Connectors
- > Market Applications > Automation > Motion Control / Servo Motors > C091 Connectors > C091 D+ > 5 Position Cable Connectors
- > Market Applications > Medical > C091 Connectors > C091 D+ > 5 Position Cable Connectors
- > Market Applications > Wireless Infrastructure > C091 Connectors > C091 D+ > 5 Position Cable Connectors

LINKS

- > Company
- > Contact
- > Privacy Policy
- > Terms and Conditions
- > Code of Business Conduct and Ethics
- > ISO Certification
- > Quality Policy
- > Industrial@Amphenol News
- > Test Reports

SHOP

- > Our Product Lines
- > Market Applications
- > Distributors

FOLLOW US!



