

HC-STA-B32-CHWD-1TTP36-ELC-AL - Housing



1424840

<https://www.phoenixcontact.com/us/products/1424840>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Coupling housings B32, with double locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, straight, 1x Pg36, height: 99.8 mm, cable gland: none, Standard

Your advantages

- Good shielding in the event of electromagnetic interference

Commercial data

Item number	1424840
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF56
Product key	BF7APB
Catalog page	Page 644 (C-2-2019)
GTIN	4055626382456
Weight per piece (including packing)	457.4 g
Weight per piece (excluding packing)	444 g
Customs tariff number	85389099
Country of origin	CN

HC-STA-B32-CHWD-1TTP36-ELC-AL - Housing



1424840

<https://www.phoenixcontact.com/us/products/1424840>

Technical data


Product properties

Product type	Housing with locking latch
Housing type	Coupling housings
Application	Standard
Type	B32
No. of cable outlets	1
Type of the screw connection	1x Pg36
Type	Tall design
Cable outlet	straight
Pg screw connection	none

Data management status

Article revision	01
------------------	----

Dimensions

Dimensional drawing	
Width	82.5 mm
Height	99.8 mm
Length	94 mm

Material specifications

Flammability rating according to UL 94	V0 (Interlock)
Seal material	NBR, conductive
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Locking latch material	PA

Mechanical properties

Mechanical data

Type of the screw connection	1x Pg36
Locking type	Latch

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP67

HC-STA-B32-CHWD-1TTP36-ELC-AL - Housing




1424840

<https://www.phoenixcontact.com/us/products/1424840>

Enclosure rating (NEMA)	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Impact strength	IK09
Ambient temperature (operation)	-40 °C ... 125 °C

Drawings

Dimensional drawing



Dimensional drawing

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1424840>

**DNV**
Approval ID: TAE000037S

**cUL Recognized**
Approval ID: E255026

**UL Recognized**
Approval ID: E255026

**EAC**
Approval ID: RU C-DE.BL08.B.00511

cULus Recognized

HC-STA-B32-CHWD-1TTP36-ELC-AL - Housing



1424840

<https://www.phoenixcontact.com/us/products/1424840>

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

ETIM 9.0	EC000437
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

HC-STA-B32-CHWD-1TTP36-ELC-AL - Housing



1424840

<https://www.phoenixcontact.com/us/products/1424840>

Accessories

HC-STA-B32-BCSFD-PL-BK - Protective cover

1424850

<https://www.phoenixcontact.com/us/products/1424850>

Protective cover B32, for double locking latch, protective cover material: PA, height: 24.8 mm, seal: no, Standard, with lanyard



WP-G HF IP66 PG36 BK - Screw connection

3240894

<https://www.phoenixcontact.com/us/products/3240894>

Cable gland, Pg thread, IP66 protection, straight



HC-STA-B32-CHWD-1TTP36-ELC-AL - Housing

1424840

<https://www.phoenixcontact.com/us/products/1424840>



WP-G HF IP69K PG36 BK - Screw connection

3240880

<https://www.phoenixcontact.com/us/products/3240880>

Cable gland, Pg thread, IP68/69k protection, straight



WP-G PP HF PG21 - Screw connection

3240992

<https://www.phoenixcontact.com/us/products/3240992>

Cable gland made from PP with Pg thread, IP65 protection



HC-STA-B32-CHWD-1TTP36-ELC-AL - Housing

1424840

<https://www.phoenixcontact.com/us/products/1424840>



WP-GA HF IP69K PG36 BK - Screw connection

3240908

<https://www.phoenixcontact.com/us/products/3240908>

Cable gland, Pg thread, IP68/69k protection, angled



WP-GR HF IP66 PG36 BK - Screw connection

3240950

<https://www.phoenixcontact.com/us/products/3240950>

Cable gland, Pg thread, IP66 protection, with strain relief



HC-STA-B32-CHWD-1TTP36-ELC-AL - Housing



1424840

<https://www.phoenixcontact.com/us/products/1424840>

WP-GR HF IP69K PG36 BK - Screw connection

3240936

<https://www.phoenixcontact.com/us/products/3240936>



Cable gland, Pg thread, IP68/69k protection, with strain relief

WP-G PP HF PG36 - Screw connection

3240994

<https://www.phoenixcontact.com/us/products/3240994>



Cable gland made from PP with Pg thread, IP65 protection

HC-STA-B32-CHWD-1TTP36-ELC-AL - Housing



1424840

<https://www.phoenixcontact.com/us/products/1424840>

WP-GT PP HF PG36 - Screw connection

3241008

<https://www.phoenixcontact.com/us/products/3241008>



Cable gland made from PP with Pg thread, rotatable, IP54 protection

WP-G BRASS IP40 PG36 - Screw connection

3241043

<https://www.phoenixcontact.com/us/products/3241043>



Cable gland made from brass with Pg thread, IP40 protection

HC-STA-B32-CHWD-1TTP36-ELC-AL - Housing



1424840

<https://www.phoenixcontact.com/us/products/1424840>

WP-GT BRASS PG36 - Screw connection

3241029

<https://www.phoenixcontact.com/us/products/3241029>

Cable gland made from brass with Pg thread, rotatable, IP40 protection



WP-G BRASS IP65 PG36 - Screw connection

3241057

<https://www.phoenixcontact.com/us/products/3241057>

Cable gland made from brass with Pg thread, IP65 protection



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com