

# M23-09P1N8A8004 - Cable connector



1629217

<https://www.phoenixcontact.com/pc/products/1629217>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, series: M23 PRO, straight, shielded: yes, Screw locking mechanism, No. of pos.: 8+1, Direction of rotation: Standard, contact connection type: Pin, Crimp connection, cable diameter range: 9 mm ... 15 mm, coding: N, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb < 0.1 %)

## Your advantages

- Solutions with cross-manufacturer compatibility for standard and fast locking systems
- Reliable under the harshest conditions: cable connectors with vibration brake
- Modern, consistent design for highly convenient operation
- Easy, cost-effective cable assembly: uniform shielding of M17 to M40

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 1629217                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Product key                          | ABRABA                         |
| Catalog page                         | Page 76 (C-2-2019)             |
| GTIN                                 | 4055626618500                  |
| Weight per piece (including packing) | 114.5 g                        |
| Weight per piece (excluding packing) | 114 g                          |
| Customs tariff number                | 85366990                       |
| Country of origin                    | DE                             |

# M23-09P1N8A8004 - Cable connector



1629217

<https://www.phoenixcontact.com/pc/products/1629217>

## Technical data

### Notes

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Order information: | Order crimp contacts 8 x Ø 1 mm, 1 x Ø 2 mm separately                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Safety note        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Safety note        | <p>WARNING: The connectors may not be plugged in or disconnected under load. Ignoring the warning or improper use may damage persons and/or property.</p> <ul style="list-style-type: none"><li>• WARNING: Commission properly functioning products only. The products must be regularly inspected for damage. Decommission defective products immediately. Replace damaged products. Repairs are not possible.</li><li>• WARNING: Only electrically qualified personnel may install and operate the product. They must observe the following safety notes. The qualified personnel must be familiar with the basics of electrical engineering. They must be able to recognize and prevent danger. The relevant symbol on the packaging indicates that only personnel familiar with electrical engineering are allowed to install and operate the product.</li><li>• The products are suitable for applications in plant, controller, and electrical device engineering.</li><li>• When operating the connectors in outdoor applications, they must be separately protected against environmental influences.</li><li>• Assembled products may not be manipulated or improperly opened.</li><li>• Only use mating connectors that are specified in the technical data of the standards listed (e.g. the ones listed in the product accessories online at <a href="https://www.phoenixcontact.com/products">phoenixcontact.com/products</a>).</li><li>• When using the product in direct connection with third-party manufacturers, the user is responsible.</li><li>• For operating voltages &gt; 50 V AC, conductive connector housings must be grounded</li><li>• Ensure that the protective or functional ground has been properly connected.</li><li>• VDE 0100/1.97 § 411.1.3.2 and DIN EN 60 204/11.98 § 14.1.3 are applicable when combining several circuits in a cable and/or connector</li><li>• Only use tools recommended by Phoenix Contact</li><li>• The installation notes/Design In documents online on the download page at <a href="https://www.phoenixcontact.com/products">phoenixcontact.com/products</a> must be observed for this product.</li><li>• Operate the connector only when it is fully plugged in and interlocked.</li><li>• Ensure that when laying the cable, the tensile load on the connectors does not exceed the upper limit specified in the standards.</li><li>• Observe the minimum bending radius of the cable. Lay the cable without twisting it.</li><li>• The connector warms up in normal operation. Depending on the ambient conditions, the surface of the connector can continue to warm up. In this case, the user is responsible for posting</li></ul> |

# M23-09P1N8A8004 - Cable connector



1629217

<https://www.phoenixcontact.com/pc/products/1629217>

warnings (e.g. DIN EN ISO 13732-1:2008-12).

## Mounting

|             |    |
|-------------|----|
| Thread type | () |
|-------------|----|

## Product properties

|              |                                 |
|--------------|---------------------------------|
| Product type | Circular connector (cable-side) |
|--------------|---------------------------------|

### Data management status

|                  |    |
|------------------|----|
| Article revision | 07 |
|------------------|----|

## Connector

### Insulating body

|                             |                                                                           |
|-----------------------------|---------------------------------------------------------------------------|
| Note                        | Order information: Order crimp contacts 8 x Ø 1 mm, 1 x Ø 2 mm separately |
| Coding                      | N                                                                         |
| Insulation body material    | PA 6.6                                                                    |
| Insertion/withdrawal cycles | 100                                                                       |
| Connection method           | Crimp connection                                                          |
| Contact switching type      | Pin                                                                       |
| Application                 | Signal                                                                    |
| Number of positions         | 9                                                                         |
| Direction of rotation       | Standard                                                                  |
| Connection profile          | 8+1                                                                       |

|                  |      |
|------------------|------|
| Contact diameter | 2 mm |
|------------------|------|

### Power contacts

|                         |                     |
|-------------------------|---------------------|
| Litz wire cross-section | 0.5 mm <sup>2</sup> |
|-------------------------|---------------------|

### Power contacts min.

|                         |                     |
|-------------------------|---------------------|
| Litz wire cross-section | 2.5 mm <sup>2</sup> |
|-------------------------|---------------------|

### Power contacts max.

|               |      |
|---------------|------|
| Rated current | 20 A |
|---------------|------|

### Power contacts

|      |                                   |
|------|-----------------------------------|
| Note | for max. connection cross section |
|------|-----------------------------------|

|               |       |
|---------------|-------|
| Rated voltage | 300 V |
|---------------|-------|

|                     |        |
|---------------------|--------|
| Rated surge voltage | 2.5 kV |
|---------------------|--------|

|                      |    |
|----------------------|----|
| Overvoltage category | II |
|----------------------|----|

|                     |   |
|---------------------|---|
| Degree of pollution | 3 |
|---------------------|---|

|                  |      |
|------------------|------|
| Contact diameter | 1 mm |
|------------------|------|

### Signal contacts

|                         |                      |
|-------------------------|----------------------|
| Litz wire cross-section | 0.08 mm <sup>2</sup> |
|-------------------------|----------------------|

### Signal contacts min.

|                         |                   |
|-------------------------|-------------------|
| Litz wire cross-section | 1 mm <sup>2</sup> |
|-------------------------|-------------------|

### Signal contacts max.

|                                    |     |
|------------------------------------|-----|
| Nominal current per signal contact | 8 A |
|------------------------------------|-----|

|      |                                   |
|------|-----------------------------------|
| Note | for max. connection cross section |
|------|-----------------------------------|

|                              |       |
|------------------------------|-------|
| Rated voltage Signal contact | 300 V |
|------------------------------|-------|

|                     |        |
|---------------------|--------|
| Rated surge voltage | 2.5 kV |
|---------------------|--------|

|                      |    |
|----------------------|----|
| Overvoltage category | II |
|----------------------|----|

|                     |   |
|---------------------|---|
| Degree of pollution | 3 |
|---------------------|---|

# M23-09P1N8A8004 - Cable connector



1629217

<https://www.phoenixcontact.com/pc/products/1629217>

|                     |        |
|---------------------|--------|
| Installation height | 2000 m |
|---------------------|--------|

## Housing

|                                   |                                |
|-----------------------------------|--------------------------------|
| Housing material                  | GD-Zn                          |
| Type of locking                   | Screw locking mechanism        |
| Pg screw connection               | none                           |
| Degree of protection (plugged in) | IP66 / IP68 (2m / 24h) / IP69K |
| Thread type                       | M23                            |

## Seal

|                         |                |
|-------------------------|----------------|
| External cable diameter | 9 mm ... 15 mm |
| Seal material           | FKM            |

## Environmental and real-life conditions

### Ambient conditions

|                                          |                                     |
|------------------------------------------|-------------------------------------|
| Ambient temperature (operation)          | -40 °C ... 105 °C (see to derating) |
| Ambient temperature (storage/transport)  | 15 °C ... 25 °C                     |
| Permissible humidity (storage/transport) | 50 % ... 65 %                       |
| Permanent temperature                    | 125 °C (DIN EN 60512-9-2 / 1000 h)  |

# M23-09P1N8A8004 - Cable connector



1629217

<https://www.phoenixcontact.com/pc/products/1629217>

## Drawings

Dimensional drawing




Dimensional drawing, housing

# M23-09P1N8A8004 - Cable connector

1629217

<https://www.phoenixcontact.com/pc/products/1629217>

Schematic diagram




Connector pin assignment

# M23-09P1N8A8004 - Cable connector



1629217

<https://www.phoenixcontact.com/pc/products/1629217>



$I$  = current strength,  $\theta$  = ambient temperature, 9x 8 A

# M23-09P1N8A8004 - Cable connector



1629217

<https://www.phoenixcontact.com/pc/products/1629217>

## Approvals

 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1629217>



**cUL Recognized**

Approval ID: E335019-20141210



**UL Recognized**

Approval ID: E335019-20141210

**cULus Recognized**

# M23-09P1N8A8004 - Cable connector



1629217

<https://www.phoenixcontact.com/pc/products/1629217>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440116 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002635 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# M23-09P1N8A8004 - Cable connector



1629217

<https://www.phoenixcontact.com/pc/products/1629217>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

# M23-09P1N8A8004 - Cable connector



1629217

<https://www.phoenixcontact.com/pc/products/1629217>

## Accessories

### SF-Z0028 - Torque screwdriver

1607456

<https://www.phoenixcontact.com/pc/products/1607456>

Torque screwdriver, series: RC, UC, SH, SF



---

### SF-Z0027 - Hook wrench

1607455

<https://www.phoenixcontact.com/pc/products/1607455>

Hook wrench, series: RC, UC, RF, SF



## M23-09P1N8A8004 - Cable connector

1629217

<https://www.phoenixcontact.com/pc/products/1629217>



## RF-Z0007 - Special wrench

1614347

<https://www.phoenixcontact.com/pc/products/1614347>

Special wrench, series: RF



---

## RC-Z2220 - Contact insertion and removal tool

1604360

<https://www.phoenixcontact.com/pc/products/1604360>

Positioning and removal tool for RC crimp contacts, pin/socket diameter: 2 mm



# M23-09P1N8A8004 - Cable connector



1629217

<https://www.phoenixcontact.com/pc/products/1629217>

## RC-Z2490 - Contact insertion and removal tool

1611803

<https://www.phoenixcontact.com/pc/products/1611803>



Positioning and unlocking tool for RC crimp contacts (D-SUB) for pin/socket, diameter: 2 mm

---

## RC-Z2097 - Contact insertion and removal tool

1604251

<https://www.phoenixcontact.com/pc/products/1604251>



Insertion and removal tool for RC crimp contacts for pin/socket, diameter: 1 mm, connection cross-section: 0.08 mm<sup>2</sup> ... 0.56 mm<sup>2</sup>

## M23-09P1N8A8004 - Cable connector

1629217

<https://www.phoenixcontact.com/pc/products/1629217>



## RC-Z2494 - Contact insertion and removal tool

1614123

<https://www.phoenixcontact.com/pc/products/1614123>



Positioning and removal tool for RC crimp contacts, pin/socket diameter: 1 mm

---

## RC-11P2000 - Crimp contact

1596770

<https://www.phoenixcontact.com/pc/products/1596770>



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: 0.08 mm<sup>2</sup> ... 0.22 mm<sup>2</sup>, Contact release tool not necessary for the 12- and 17-pos. crimp versions of the M23-PRO series, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1240882

# M23-09P1N8A8004 - Cable connector



1629217

<https://www.phoenixcontact.com/pc/products/1629217>

## RC-12P2000 - Crimp contact

1597862

<https://www.phoenixcontact.com/pc/products/1597862>



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: 0.14 mm<sup>2</sup> ... 0.56 mm<sup>2</sup>, Contact release tool not necessary for the 12- and 17-pos. crimp versions of the M23-PRO series, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1240882

---

## RC-1KP2000 - Crimp contact

1602996

<https://www.phoenixcontact.com/pc/products/1602996>



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: 0.5 mm<sup>2</sup> ... 1 mm<sup>2</sup>, Contact release tool not necessary for the 12- and 17-pos. crimp versions of the M23-PRO series, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241571

## M23-09P1N8A8004 - Cable connector

1629217

<https://www.phoenixcontact.com/pc/products/1629217>



### RC-22P2000 - Crimp contact

1603321

<https://www.phoenixcontact.com/pc/products/1603321>



Crimp contact, Pin, rolled, Single contact, contact diameter: 1 mm, crimp range: 0.22 mm<sup>2</sup> ... 0.56 mm<sup>2</sup>, Single contact, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb < 0.1 %)

---

### RC-22P2300 - Crimp contact

1603324

<https://www.phoenixcontact.com/pc/products/1603324>



Crimp contact, Pin, rolled, Taped product, number of pieces per reel: 500, contact diameter: 1 mm, crimp range: 0.22 mm<sup>2</sup> ... 0.56 mm<sup>2</sup>, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb < 0.1 %)

# M23-09P1N8A8004 - Cable connector



1629217

<https://www.phoenixcontact.com/pc/products/1629217>

## RC-22P2400 - Crimp contact

1603325

<https://www.phoenixcontact.com/pc/products/1603325>



Crimp contact, Pin, rolled, Taped product, number of pieces per reel: 10000, contact diameter: 1 mm, crimp range: 0.22 mm<sup>2</sup> ... 0.56 mm<sup>2</sup>, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb < 0.1 %)

---

## RC-21P2000 - Crimp contact

1603310

<https://www.phoenixcontact.com/pc/products/1603310>



Crimp contact, Pin, rolled, Single contact, contact diameter: 1 mm, crimp range: 0.08 mm<sup>2</sup> ... 0.22 mm<sup>2</sup>, Single contact

# M23-09P1N8A8004 - Cable connector



1629217

<https://www.phoenixcontact.com/pc/products/1629217>

## RC-21P2300 - Crimp contact

1603313

<https://www.phoenixcontact.com/pc/products/1603313>



Crimp contact, Pin, rolled, Taped product, number of pieces per reel: 500, contact diameter: 1 mm, crimp range: 0.08 mm<sup>2</sup> ... 0.22 mm<sup>2</sup>

---

## RC-21P2400 - Crimp contact

1611637

<https://www.phoenixcontact.com/pc/products/1611637>



Crimp contact, Pin, rolled, Taped product, number of pieces per reel: 10000, contact diameter: 1 mm, crimp range: 0.08 mm<sup>2</sup> ... 0.22 mm<sup>2</sup>

# M23-09P1N8A8004 - Cable connector



1629217

<https://www.phoenixcontact.com/pc/products/1629217>

## RC-5SP2000 - Crimp contact

1603529

<https://www.phoenixcontact.com/pc/products/1603529>



Crimp contact, Pin, turned, contact diameter: 2 mm, crimp range: 0.5 mm<sup>2</sup> ... 0.75 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241632

---

## RC-59P2000 - Crimp contact

1603498

<https://www.phoenixcontact.com/pc/products/1603498>



Crimp contact, Pin, turned, Single contact, contact diameter: 2 mm, crimp range: 0.75 mm<sup>2</sup> ... 1 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241632

# M23-09P1N8A8004 - Cable connector



1629217

<https://www.phoenixcontact.com/pc/products/1629217>

## RC-5CP2000 - Crimp contact

1603513

<https://www.phoenixcontact.com/pc/products/1603513>



Crimp contact, Pin, turned, contact diameter: 2 mm, crimp range: 1 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241634

---

## RC-5AP2000 - Crimp contact

1603505

<https://www.phoenixcontact.com/pc/products/1603505>



Crimp contact, Pin, turned, contact diameter: 2 mm, crimp range: 1.5 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1241634

# M23-09P1N8A8004 - Cable connector

1629217

<https://www.phoenixcontact.com/pc/products/1629217>



## PROT-M23PRO-SG-IT-IP20 - Plastic protective cap

1055744

<https://www.phoenixcontact.com/pc/products/1055744>

Plastic protective cap, M23, degree of protection: IP20, series: M23 PRO Signal



---

## PROT-M23PRO-SG-IT-IP67 - Plastic protective cap

1055745

<https://www.phoenixcontact.com/pc/products/1055745>

Plastic protective cap, M23, degree of protection: IP67, series: M23 PRO Signal



---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)