Power Double Lock

TE Internal #: 1-179466-5

Housing, Receptacle, Wire-to-Wire, 6 Position, 3.96 mm [.156 in]

Centerline, Wire & Cable, UL 94V-0, Power Double Lock,

Rectangular Power Connectors

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors











Rectangular Power Connector Type: Housing

Connector & Housing Type: Receptacle

Connector System: Wire-to-Wire

Number of Positions: 6

Centerline (Pitch): 3.96 mm [.156 in]

Features

Product Type Features

Compatible With Discrete Wire Type	Stranded
Rectangular Power Connector Type	Housing
Connector & Housing Type	Receptacle
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	6
Number of Power Positions	0
Number of Signal Positions	0
Number of Rows	2
Electrical Characteristics	

300 VAC

Operating Voltage



Contact Retention Within Housing Contact Type Termination Features Termination Method to Wire & Cable Mechanical Attachment Connector Mounting Type	Matrix Without Tab Crimp
Contact Type Termination Features Termination Method to Wire & Cable Mechanical Attachment Connector Mounting Type	Tab
Termination Features Termination Method to Wire & Cable Mechanical Attachment Connector Mounting Type	
Termination Method to Wire & Cable Mechanical Attachment Connector Mounting Type	Crimp
Mechanical Attachment Connector Mounting Type	Crimp
Connector Mounting Type	
	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	3.96 mm[.156 in]
Housing Color	Black
Housing Material	Nylon
Dimensions	
Connector Height	13.2 mm
Product Width	13.9 mm
	26.1 in
Row-to-Row Spacing	4.6 mm[.181 in]
Usage Conditions	
Operating Temperature Range	-30 – 105 °C[-22 – 221 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Compatible With Agency/Standards Products	UL
Compatible With Approved Standards Products	UL 1977
UL Flammability Rating	UL 94V-0
Glow Wire Rating	Standard Part - Not Glow Wire
Packaging Features	
Packaging Quantity	150
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts













Also in the Series | Power Double Lock





Connector Contacts(24)



Connector Hardware(14)



Insertion & Extraction Tools(2)



Customers Also Bought















Documents

Product Drawings

AMP POWER DBL LOCK CAP HSG 6P Black

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-179466-5_P.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-179466-5_P.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-179466-5_P.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Housing, Receptacle, Wire-to-Wire, 6 Position, 3.96 mm [.156 in] Centerline, Wire & Cable, UL 94V-0, Power Double Lock, Rectangular Power Connectors



Product Specifications

Application Specification

English

Agency Approvals

CSA Certificate

English