



- A computer with a DisplayPort v1.2 compatible Graphics Card (e.g. AMD Radeon with AMD Eyefinity technology) is required to display in video wall mode. Backward compatible with most DisplayPort 1.1a equipment running current graphics drivers, with the feature set being limited to that of your equipment (e.g. you may be limited to displaying in Clone / Mirror mode only). Compatibility with older graphics cards is not guaranteed.
- Maximum supported video resolutions and number of monitors will be dependent upon your graphics card. Check the specifications of your graphics card to determine its capabilities.

2-Port DisplayPort 1.2 Multi-Stream Transport (MST) Hub, 3840 x 2160 4Kx2K UHD, TAA

MODEL NUMBER: B156-002







Description

Get everyone's attention by broadcasting awesome messages in ultra-high definition video! With Tripp Lite's B156-002 2-Port Multi-Display Video Splitter/Expander, you can split or expand a single DisplayPort signal into two separate signals and display them on two DisplayPort monitors using standard DisplayPort cables (Tripp Lite P580-Series or P583-Series). You can display the same image on each monitor, extend the desktop across them, or display in video wall mode where monitors are combined to display as one, enlarged monitor. The B156-002 supports 4Kx2K Ultra-High Definition (UHD) video resolutions up to 3840x2160 (24 and 30Hz), 48-bit Deep Color (16 bits per channel), and is compatible with HDCP, EDID and DDC. It is compliant with DisplayPort v1.2. It comes with an external power supply and brackets for wall-, rack- or pole-mounting. All mounting hardware is included. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Features

Splitting, Extending, Multi-Display

- Splits a DisplayPort video signal to simultaneously display the same signal on two DisplayPort monitors, or expands it across both monitors as in video wall mode
- Displays can be placed up to 25 ft. away from the splitter/expander; the video source can be up to 16 ft. away from the splitter/expander (6 ft. is recommended).

Highlights

- Compliant with DisplayPort 1.2
- Splits or expands a DisplayPort audio/video signal on two DisplayPort monitors
- Display the same image on each monitor, extend the desktop across them, or display in video wall mode where monitors are combined to display as one
- Supports 4K x 2K Ultra High Definition (UHD) video resolutions up to 3840 x 2160 (24 and 30 Hz) - see System Requirements
- Supports up to 48-bit Deep Color (16 bits per channel)
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

System Requirements

- A computer with a DisplayPort v1.2 compatible Graphics Card (e.g. AMD Radeon with AMD Eyefinity technology) is required to display in video wall mode.
- Mac OS X does not support MST for NVIDIA and Intel Graphics Processor Units, limiting video display on the connected monitors to mirror
- Backward compatible with most
 DisplayPort 1.1a equipment
 running current graphics drivers,



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

 Supports both 4Kx2K (3840x2160 at 24 and 30Hz) UHD video and standard 1080p (1920x1080 at 60Hz) high-definition video

Video Standards and Protocols

- Supports up to 48-bit Deep Color (16 bits per channel) and video resolutions up to 4K Ultra High Definition (UHD), 3840x2160 (24 and 30Hz)
- Complies with HDCP, EDID and DDC
- Compatible with DisplayPort 1.2
- Compatible with Apple® Thunderbolt connectors (using P583-Series Mini Displayport to Displayport adapter cable)

Installation

- Plug-and-play; no software or drivers required
- Easy to install; connect the DisplayPort video source to the hub's input port, connect the external power supply, and finally connect the two monitors to the output ports

Mounting Options

• Wall-, rack- or pole-mounting; all mounting hardware is included

TAA-Compliant for GSA Schedule Purchases

• Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

with the feature set being limited to that of your equipment (e.g. you may be limited to displaying in Clone / Mirror Mode only).

Compatibility with older graphics cards is not guaranteed.

- Maximum supported video
 resolutions and number of
 monitors will be dependent upon
 your graphics card. Check the
 specifications of your graphics
 card to determine its
 capabilities.
- A monitor with a Displayport input port.
- For international use, the B110-INT power supply can be purchased separately; it features plugs for the UK,
 Europe, and Australia

Package Includes

- B156-002 Multi-Display
 Splitter/Expander
- Mounting hardware
- Bracket (for wall-, rack- or polemounting)
- External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2A, 5 ft.)

Specifications

MODEL TEXT	
What Does This Product Do?	Ideal for digital signage at schools, airports and other public venues that require a DisplayPort video signal to appear on two separate DisplayPort monitors or expanded across both monitors as a video wall.





OVERVIEW		
-		
AC Adapter	Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2A, 5 ft.	
PHYSICAL		
Unit Dimensions (hwd / in.)	1.00 x 3.60 x 2.52	
Unit Dimensions (hwd / cm)	2.54 x 9.144 x 6.4	
Unit Weight (lbs.)	1	
Unit Weight (kg)	0.45	
Color	Black	
CONNECTIONS		
Ports	2	
Side A - Connector 1	DISPLAYPORT (FEMALE)	
Side B - Connector 1	(2) DISPLAYPORT (FEMALE)	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies