





4-Port VGA/SVGA Video Splitter with Signal Booster, High Resolution Video, 350MHz, (HD15 M/4xF)

MODEL NUMBER: B114-004-R







Description

Tripp Lite's 4-Port VGA/SVGA Video Splitter provides bandwidth support at 350MHZ, allowing simultaneous display of video on up to 4 monitors. In addition, a built-in booster allows a video signal (up to 2048 x 1536 @ 60Hz) to be transmitted up to 210 ft. from the source. Four standard HD15 female ports are used to connect the monitors, while a fifth HD15 male port is used to connect the CPU. The splitter can be located up to 25 ft. from the connected computer, and up to 185 ft. from the connected monitors. The number of connected monitors can be expanded by cascading up to 3 levels of B114-004-R splitters together.

Features

- Simultaneously display video on up to 4 VGA/SVGA monitors
- Ideal for video presentations or sharing information with multiple users
- A built-in booster allows a video signal (up to 2048 x 1536 @ 60Hz) to be transmitted up to 210 ft. from the source
- The splitter can be located up to 25 ft. from the connected computer, and up to 185 ft. from the connected monitors
- 350Mhz Bandwidth Support
- · Cascade up to 3 levels of B114-004-R splitters together to increase the number of connected monitors
- · Rugged, fully shielded metal housing

Specifications

INPUT

Highlights

- Simultaneously displays video on up to 4 VGA/SVGA monitors
- · A built-in booster allows a video signal (up to 2048 x 1536 @ 60Hz) to be transmitted up to 210 ft. from the source
- The splitter can be located up to 25 ft. from the connected computer, and up to 185 ft. from the connected monitors
- 350Mhz bandwidth support

System Requirements

- · Computer with an HD15 port
- VGA/SVGA monitor
- B114-004-R can only be cascaded with other B114-004-R splitters

Package Includes

- B114-004-R VGA/SVGA Video Splitter - 4 Port
- External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 0.3A; Output: 9V, 1A)
- Owner's manual





100; 110; 120; 127; 200; 208; 220; 230; 240	
100-240V / 50/60Hz / 0.4A	
9V / 1A	
5	
OD: 5.5 x 2.1 x 12mm, Positive Pin, Negative Sleeve	
NEMA 1-15P North America	
FCC; UL; cUL; RoHS	
TROLS	
Green (Power)	
2.4 x 9.8 x 5.9	
2.00	
Вох	
1.7 x 5.2 x 3.7	
1.00	
0.45	
Iron	
Black	
ENVIRONMENTAL	
32 to 122 F (0 to 50 C)	
-4 to 140 F (-20 to 60 C)	
0% to 80% RH, Non-Condensing	
6.1 BTU/Hr	
1.8	
COMMUNICATIONS	
210	
64	
CONNECTIONS	
4	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

Side B - Connector 1	(4) HD15 (FEMALE)	
Connector Plating	Nickel	
PORT EXPANSION		
Max Distance (Between any 2 Units)	246ft (75m)	
Max Number of Ports (Entire Chain)	64	
FEATURES & SPECIFICATIONS		
Max Supported Video Resolution	2048 x 1536 @60Hz	
Driver Required	No	
EDID Compatible	Yes	
CERTIFICATIONS		
Certifications	Tested to CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies